

POLYFLOR CAMARO WOOD PUR

- Camaro - collection of versatile vinyl floor products
- Wood effect floorcovering designs
- Coordinating grouting, marquetry and feature strips are readily available to blend, shape or accentuate design ideas

SPECIFICATION



2.0mm



0.3mm



36 @ 101 x 914mm = 3.34m<sup>2</sup>  
 24 @ 152 x 914mm = 3.34m<sup>2</sup>  
 18 @ 152 x 1219mm = 3.34m<sup>2</sup>  
 14 @ 203 x 1219mm = 3.46m<sup>2</sup>



3600g/m<sup>2</sup>



**GENERAL PERFORMANCE**  
 EN 649  
 EN ISO 10582



**REACTION TO FIRE**  
 EN 13501-1 Class Bfl-S1



**ABRASION RESISTANCE**  
 EN 649 Group T  
 EN ISO 10582 Type 1



**SLIP RESISTANCE\***  
 EN 13893 Class DS (dry condition)  
 DIN 51130 R10  
 AS/NZS 4586 R10

For safety flooring with sustainable wet slip resistance, refer to Expona Control PUR or the Polysafe ranges



**INDENTATION - RESIDUAL**  
 EN 433 <0.05mm  
 EN ISO 24343-1 ≤ 0.05mm



**DIMENSIONAL STABILITY**  
 EN 434 <0.1%  
 EN ISO 23999 ≤ 0.1% max.



**CASTOR CHAIR (continuous use)**  
 EN 425 / ISO 4918 Suitable



**THERMAL CONDUCTIVITY**  
 Suitable for underfloor heating heating Max 27°C



**LIGHT FASTNESS**  
 ISO 105-B02 (Method 3) ≥6



**RESPONSIBLE SOURCING**  
 BES 6001 Very good  
 SA 8000 Approved factory



**ELECTRICAL BEHAVIOUR (body voltage)**  
 EN1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.



**VOC EMISSIONS**  
 Indoor Air Comfort GOLD - Eurofins certified product  
 AgBB - Very low emissions  
 FloorScore - Certified product



**PREFERABLE FLOORING**  
 Polyflor Camaro PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 429). Generic EN 15804 Environmental Product Declaration (EPD) available on request. Camaro PUR is 100% recyclable and contains average 40% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/environment](http://www.polyflor.com/environment)



Camaro PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention.



**APPLICATIONS**  
 Camaro PUR is suitable for use in any domestic situation and moderate commercial areas such as offices, hotels and boutiques.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com).

\* For clarification regarding slip resistance, consult Polyflor.  
**VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.**



CAMARO™  
 FLOORING COLLECTION


WOOD



PERFORMANCE AND PROPERTIES



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFM), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK  
 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551  
 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912  
 RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128  
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: [INFO@POLYFLOR.COM](mailto:INFO@POLYFLOR.COM)  
 WEBSITE: [WWW.POLYFLOR.COM](http://WWW.POLYFLOR.COM)

