



The Forest fx collection of wood effect vinyl sheet floorcoverings is specifically designed for a wide range of commercial interiors. The contemporary and creative timber designs are ideal for education, healthcare, office, retail and leisure sectors, developed and presented in a practical, resilient and hygienic product construction.

Adding to the established success of the collection, the top selling designs have been joined by fresh and exciting effects creating a varied and authentic wood palette, demonstrated by the intricate grains and natural colour ways.

The durability of Forest fx lends itself perfectly to the demands of commercial interiors, leading with the key advantages of aesthetics and performance, with the added flexibility to meet corporate design schemes. Unique floor designs can easily be achieved by incorporating inlaid features and logos, managed by Polyflor's in house design team.

To further enhance the floorcovering, Forest fx features a high quality, cross-linked polyurethane reinforcement (PUR) providing a low cost, polish-free maintenance regime for the lifetime of the product.

Forest fx is 100% recyclable and achieves BRE A+ certification for major use areas based on a life cycle analysis approach over a building life of 60 years. All these qualities make the collection environmentally preferable whilst meeting decorative, practical, budgetary and maintenance objectives.

For more details on these or any other Polyflor products visit www.polyflor.com.











° Refer to BRE Global ratings on www.greenbooklive.com





WARM BEECH

The smooth, linear grain pattern found in Warm Beech makes this design ideal for larger spaces, whilst the tonal contrast gives the design further depth and detailing.



Also available as an **19dB** acoustic option



OILED OAK

Oak is a highly popular design in both commercial and domestic interiors, which is unsurprising given its versatility and strong design.

This Oiled Oak example gives a more contemporary look to a traditional material, without affecting the impact of the natural wood grain.



Also available as an acoustic option



Wide plank design



AMERICAN OAK

American Oak takes the traditional oak pattern and incorporates a smoother grain and warming honey tone to give the flooring a clean and contemporary look.



Also available as an acoustic option







Also available as an acoustic option



Wide plank design





EUROPEAN OAK

Encapsulating deep honey tones with a subtle, smooth wood grain, the European Oak pattern is suited to a wide range of interiors, and it's easy-clean features makes it a practical floorcovering option.



Also available as an acoustic option













Wide plank design




3230 Classic Walnut





BRAZILIAN WALNUT

The intence brown and red hues together with a rustic grain gives Brazilian Walnut a distinct quality and character suited to more intimate settings and high-design interiors.



40


Forest fx

FEATURES









HEALTH & SAFETY





Indoor air quality is, quite rightly, a key environmental consideration when selecting building products. The Forest fx range when tested to the AgBB method, achieves VOC (volatile organic compounds) emissions below quantifiable levels (trakett statement). The collection has also attained Eurofins Indoor Air Comfort Gold status and FloorScore certification.

Health & Safety is also a factor when selecting the right floorcovering for any installation. Forest fx is certified to R10 (DIN 51130 and EN 13893 Class DS). If safety flooring with sustainable wet slip resistance is required Polyflor also offers wood effect Polysafe designs (see page 43).

ENVIRONMENT



Polyflor have demonstrated a high level of commitment over the years to minimising our impact on the environment without compromising the performance benefits of our high quality floorcoverings.

There can be few materials better suited to recycling than vinyl flooring. Forest fx is 100% recyclable, and can be recycled many times without loosing any of its performance properties. Polyflor continually works on developing new products and technologies, and constantly evaluates production methods to further minimise our impact on the environment.

MAINTENANCE & HYGIENE



The incorporation of a polyurethane reinforcement into the Forest fx collection helps protect the floorcovering by resisting soiling and scuffing. Combined with the superior closed surface finish, this enhanced protection allows the use of a polish-free maintenance regime for the lifetime of the flooring.

This leads to an overall maintenance cost saving of 48% over a 20+ year life when compare to untreated heterogeneous flooring, and fewer cleaning chemicals and reduced power requirements mean reduced environmental impact.

BRE GLOBAL RATINGS



The Forest fx range has been individually assessed by GRE Global and has achieved the highest possible A+rating (Certificate No: ENP 415) when used in major sectors such as healthcare, education and retail.

BRE's assessment is based on a life cycle analysis approach over a building life of 60 years, to ensure that products meet performance standards appropriate for their intended use. This independent assessment and certification can help the specifier sift through the various claims and counter claims that exist in the marketplace for environmental performance.

° Refer to BRE Global ratings on www.greenbooklive.com

42 43

Forest fx

APPLICATIONS

OTHER RANGES









DESIGN SERVICE

Polyflor has over 20 years experience in delivering floor design solutions. From simple tile patterns, borders and compass designs, to custom cut motifs.

We've helped architects and designers to realise stunning floors for hundreds of buildings, and our designers provide support throughout the project offering visuals, colour and product advice.

There is virtually no limit to the shapes, patterns or pictures you can create. We offer the precision and the flexibility of waterjet cutting to produce any design you require. School badges, information signs, corporate motifs; the possibilities are endless.

FIT FOR PURPOSE

In some large scale commercial interiors where the area is dual-purpose, the use of different types of floorcovering can help outline each zone to guide users.

For interiors where slip resistance is vital but only in certain zones, for example a school canteen, combining Polysafe slip resistant flooring in the food serving area with Forest fx wood effect in the dining area can help distinguish each of these zones, ensure Health & Safety is adhered to, and create a welcoming dining room for the children to relax in.

Acoustix Forest fx Acoustix Gallery fx

The Acoustix Forest fx and Acoustix Gallery fx collections of authentic and sophisticated wood plank and mineral designs have been developed to enhance interior installations where high quality, high design and acoustic performance is essential.

Suitable for use in a wide range of residential and commercial interiors, both the Acoustix Forest fx and Acoustix Gallery fx ranges feature a closed-cell foam backing to deliver the necessary performance to achieve an **impact sound reduction level of at least 19dB***, exceeding current building regulations.

Wood fx

Wood fx Acoustix

Polysafe Wood fx PUR brings safety, design and easy cleanability together in perfect harmony. Replicating a mix of contemporary wood styles, the range offers an unrivalled combination of high aesthetics, design clarity and built-in slip resistance that's fully HSE Compliant.

For installations where slip resistance and acoustic performance are key specification requirements, many of the shades within the Polysafe Wood fx PUR collection are also available as an acoustic option. The integrated foam backing gives Polysafe Wood fx Acoustix PUR enhanced acoustic performance with an impact sound reduction level of at least 19dB*.

^{*} For more information, visit www.polyflor.com

44

Forest fx

COLLECTION

Forest fx represents the natural beauty and sophistication of wood in a practical and durable vinyl sheet format. This contemporary and wide-ranging palette is further enhanced by a variety of plank sizes, each carefully designed for natural authenticity.



3090 Vermont Maple w/r 3290 Plank size: 100 x 500mm Also available as an acoustic option



3290 Warm Beech w/r 3290 Plank size: 100 x 500mm Also available as an acoustic option




3380 American Oak w/r 3380 Plank size: 100 x 1000mm Also available as an acoustic option



3330 Rustic Oak w/r 3330 Plank size: 84 x 332/664mm Also available as an acoustic option



3340 European Oak Plank size: 100 x 1000mm Also available as an acoustic option



Plank size: 100 x 500mm





3110 Stained Maple Plank size: 100 x 500mm Also available as an acoustic option



w/r 3360

3360 Mahogany Plank size: 84 x 332/664mm



3990 Brazilian Walnut w/r 3990 Plank size: 133 x 1000mm



Wide plank designs



2990 Oiled Oak w/r 2990 Plank size: 167 x 1500mm Also available as an acoustic option



3100 Classic Oak w/r 3330 Plank size: 167 x 1500mm Also available as an acoustic option



3120 French Walnut Plank size: 167 x 1000mm

w/r 3120



3150 Smoked Oak Plank size: 167 x 1500mm Also available as an acoustic option



3230 Classic Walnut w/r 3230 Plank size: 167 x 1000mm Also available as an acoustic option



For acoustic options see Acoustix Forest fx and Acoustix Gallery fx ranges.

SAMPLES

With regards to each design, it is only possible to give a provisional representation of the colour. To replicate the natural material, products may contain knots or markings as part of their design. For colour selection, an original sample is recommended which we will be happy to supply.

To request individual product samples of any design within the Forest fx collection, visit www.polyflor.com and follow the link to Samples and Literature. Alternatively, call the dedicated Polyflor Samples Hotline on +44 (0) 161 767 2551.



Forest fx

WELD RODS

Each of the colours within our weld rod collection has been specifically developed to match a specific Forest fx design, to achieve a clean and professional finish in every installation.

The use of weld rods also prevents the ingress of dirt and bacteria into seams and provides a floor surface which is impermeable to water for a long lasting result.

2990 used for Oiled Oak
3290 used for Warm Beech & Vermont Maple
3380 used for American Oak
3330 used for Rustic Oak & Classic Oak
3340 used for European Oak
3310 used for Rich Cherry
3110 used for Stained Maple
3150 used for Smoked Oak
3120 used for French Walnut
3230 used for Classic Walnut
3360 used for Mahogany

TECHNICAL

Specifications	Standards	Forest fx
Type of Floorcovering	EN 649	Heterogeneous
	EN ISO 10582	Heterogeneous
Product Enhancement		PUR
Gauge	EN 428	2.0mm
	EN ISO 24346	
Wear Layer	EN 429 EN ISO 24340	0.7mm
Performance Classification	EN 685 EN ISO 10874	23, 34, 43
Roll Size	EN 427 EN ISO 24341	2m x 20m = 40m ²
Total Weight	EN 430	2,700g/m²
	EN ISO 23997	
Residual Indentation	EN 433 EN ISO 24343-1	≤ 0.1mm
Abrasion Resistance	EN 649	Group T
	EN ISO 10582	Type 1
Dimensional Stability	EN 434 EN ISO 23999	≤ 0.40%
Behaviour to Fire	EN 13501-1	Bfl-S1
Slip Resistance	DIN 51130	R10 For safety flooring with sustainable wet slip resistance, refer to the Polysafe ranges.
	EN 13893	DS (Dry Slip)
Light Fastness	ISO 105-B02(Method3)	≥6
Resistance to Chemicals	EN 423 (ASTM F 1303-99)	Excellent
Underfloor Heating Suitability		Suitable, Max 27°C
Castor Chair Suitability	EN 425 ISO 4918	Yes, type W, EN 12 529
VOC Test	Indoor Air Comfort Gold AgBB FloorScore Swedish B.P.D. (FLEC test) GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Very low emissions Certified product Best class Compliant
Electrical Behaviour (body voltage)	EN1815	This product does not accumulate static charges above 2k and is classified as 'antistatic'. For specialist applications where there is requirement to dissipate the electrostatic charge, see the Polyflor ESD product range.
Hygiene	This product has been independently tested and results demonstrate that it inhibits the growth of MRSA. An effective cleaning regime is however, the most important defence against infection.	
Environmentally Preferable Flooring	Polyflor Forest fx PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 41 in major use areas such as education and healthcare. Polyflor Forest fx PUR is 100% recyclable A full Environmental Report detailing Polyflor's achievements in areas such as recycling, energy reduction and waste avoidance can be found at www.polyflor.com/environment.	















POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR LIK TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551 EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912 UK FAX: +44 (0)161 767 1128 EXPORT FAX: +44 (0)161 767 1166 ames Halitead"

E-MAIL: INFO@POLYFLOR.COM WEBSITE: WWW.POLYFLOR.COM



