



- The Polyflor PUR range of products incorporates a polyurethane reinforcement, which protects the floorcovering by resisting soiling and scuffing. Combined with the superior closed surface finish, this enhanced protection allows the use of a polish-free maintenance regime. This protection ensures that the intensity of the maintenance and overall cleaning costs are significantly reduced.

The following maintenance instructions are designed to maximise the benefits of the PUR, resulting in lower maintenance costs, without compromising the long-term appearance of your floorcovering.



**INITIAL CONSTRUCTION CLEAN**

- Remove all loose debris.
- Ensure that all traces of adhesive are removed from the surface of the floorcovering.
- Mop sweep or vacuum to remove dust and grit.
- Damp mop with a neutral detergent.
- If required, dry buff with a 1000 rpm plus rotary machine fitted with a suitable clean pad.



**ROUTINE MAINTENANCE**

- The following recommendations are provided as a guideline, and the frequency can be changed to optimise the appearance.

**DAILY**

- Mop sweep or vacuum to remove dust and loose dirt.
- If required, spot mop to remove stubborn marks, with a neutral cleanser.

**WEEKLY**

- Assess the appearance of the floor. Undertake the following as required:
- Light scuffing - dry buff with a 1000 rpm plus rotary machine fitted with a suitable clean pad.

OR

- Heavier scuffing - spray clean using a floor maintainer and 1000 rpm plus rotary machine fitted with a suitable clean pad.

**PERIODICALLY**

- Assess the appearance of the floor. If the floor has dirt build-up, machine scrub with a scrubber dryer (approx 165 rpm) fitted with a suitable clean pad, using a neutral or alkaline cleanser, as appropriate.
- Rinse thoroughly and allow to dry.
- Dry buff to restore finish.



- The maintenance regime requires the installation of an effective barrier matting system.
- Always follow the Health and Safety guidance provided, and dilute cleaners and detergents in accordance with the manufacturers' instructions.
- For recommended products, see the Polyflor Approved Maintenance Products sheet.
- Fit protective feet to table and chair legs, to prevent scratching.
- Polyflor homogeneous PUR, heterogenous PUR and Polysafe safety flooring ranges are compatible for use with the most commonly used alco-based hand gels.
- Polyflor homogeneous PUR ranges are suitable for steam cleaning on a periodic basis.
- These maintenance instructions are intended for the PUR Range of floorcoverings, which have a polyurethane reinforcement. For other Polyflor products, reference should be made to their specific floorcare sheets.

**NOTE:** In most instances, the above maintenance regime will be sufficient to ensure your floorcovering retains the optimum appearance. However where there is no mechanical means of maintaining the floor an emulsion floor polish should be applied.

- Details of the procedure to be used can be found in the Polyflor Technical Information Manual. For a copy, or further information, contact Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.
- At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.

**REGULAR CLEANING IS MORE BENEFICIAL TO THE FLOORCOVERING AND MORE COST-EFFECTIVE THAN OCCASIONAL HEAVY CLEANING.**

POLYFLOR  
**PUR RANGE**

FLOORCARE FOR  
PEARLAZZO PUR,  
PRESTIGE PUR,  
MYSTIQUE PUR,  
CLASSIC MYSTIQUE PUR  
AND 2000 PUR

