

SPORT67

- Heavy-duty, flexible vinyl sheet sports flooring
- Designed to perform safely and effectively in 'multi-purpose' indoor sports venues

SPECIFICATION



6.7mm



2m x 18.5m = 37m²



Plain colours 4260g/m²



Maple 4510g/m²



GENERAL PERFORMANCE

Tested in accordance with EN 14904

SHOCK ABSORPTION

EN 14808 Pass

BALL REBOUND

EN 12235 Pass

VERTICAL DEFORMATION

EN 14809 Pass

SLIDING COEFFICIENT OF FRICTION

EN 13036-4 Pass



REACTION TO FIRE

EN 13501-1 Class Cfl-S1 { EN ISO 9239-1 >4.5kw/m²
EN ISO 11925-2 Pass



SLIP RESISTANCE

EN 13893 Class DS



ABRASION RESISTANCE

EN 660-2 Group T
EN ISO 5470-1 <1000mg



IMPACT RESISTANCE

EN 1517 Pass



RESISTANCE TO INDENTATION

EN 1516 Pass



LIGHT REFLECTANCE VALUES

ISO 2813 ≤30



ROLLING-LOAD RESISTANCE

EN 1569 Pass



ELECTRICAL BEHAVIOUR (BODY VOLTAGE)

EN 1815 This product does not accumulate static charges above 2kV and is classified as 'antistatic'.



BIOACTIVITY

Will not support the growth of bacteria and fungi.



APPLICATIONS

Polyflor Sport is recommended for use in school and local authority sports halls, gymnasia and leisure centres where a degree of resilience underfoot and long life under heavy traffic are needed.



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Support on +44 (0)161 767 1912, or email tech@polyflor.com.



POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
 TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
 EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
 UK SAMPLE REQUESTS: +44 (0)161 767 2551



POLYFLOR

SPORT67

PERFORMANCE AND PROPERTIES

