The Polyclad range of wall and ceiling coverings are a homogeneous PVC vinyl sheet featuring a subtle marbleised decoration with the protection of a polyurethane surface treatment.

The following maintenance instructions are designed to minimise the cost factor, without compromising the long-term appearance of your wallcovering.

General advice

- Regular cleaning is more beneficial to the wallcovering and more cost-effective than occasional heavy cleaning
- Always follow the Health & Safety guidance provided and dilute cleaners and detergents in accordance with the manufacturers' instructions
- Do not use strong kitchen detergents on vinyl surfaces
- For recommended products, see the Polyflor Approved Maintenance Products sheet

After installation, including welding, is completed, the material should be left for 24 hours before any cleaning is carried out

Daily Maintenance

- For light soiling wipe the walls with a damp cloth, using a neutral cleanser diluted to the manufacturer's instructions
- Never use an abrasive pad

Routine and Periodic Maintenance

- If heavily soiled, especially with grease, wipe the walls with a damp cloth, using an alkaline cleanser diluted to the manufacturer's instructions
- Afterwards, rinse the walls using clean warm water and a small amount of neutralising agent such as acetic acid

Steam Cleaning

The Polyclad range of wall and ceiling coverings are suitable for steam cleaning on a periodic basis.

For further information and advice on specific applications, consult Polyflor Customer Technical Services on +44 (0)161767 1912, or email tech@polyflor.com.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK SALES DIRECT: +44 (0)161 767 1122 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166 E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM
UK SAMPLE REQUESTS: +44 (0)161 767 2551





WALL CLADDING

MAINTENANCE
INSTRUCTIONS FOR
POLYCLAD PU,
POLYCLAD PLUS PU
AND POLYCLAD PRO PU

