

POLYSAFE MODENA PUR



2.0mm



0.7mm



2m x 20m = 40m²



2780g/m²



GENERAL PERFORMANCE

EN 13845
ASTM F1303



REACTION TO FIRE

EN 13501-1 Class Bfl-s1
ASTM E648 Class 1



ABRASION RESISTANCE

EN 13845 50,000 cycles
EN 649 Group T



ENHANCED SLIP

Sustainable wet slip resistance*
EN 13845 ESf

AS/NZS 4586 R10

RRL Pendulum Test ≥36 (wet test - 4S Rubber/Slider 96)

Surface roughness Rz ≥20µm

The slip resistance across all Polysafe products is assured throughout the guaranteed life of the product, with strict adherence to HSE Guidelines.



VOC EMISSIONS

Indoor Air Comfort GOLD
- Eurofins certified product
AgBB Very low emissions
FloorScore certified



AGRÉMENT ASSURANCE

Independently assessed by the BBA and awarded a 10 year product performance assurance in recommended use areas.



ENVIRONMENTALLY PREFERABLE FLOORING

Polysafe Modena PUR achieves BRE Global Environmental Generic A+ rating in major use areas such as education and healthcare. Generic EN 15804 Environmental Product Declaration (EPD) available on request. It is 100% recyclable and contains recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/environment



HYGIENE

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



ELECTRICAL BEHAVIOUR

(body voltage)

EN 1815 ≤2kV Classified as 'antistatic'



Polysafe Modena PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide superior cleaning benefits, life cycle maintenance savings and optimum appearance retention. As with all Polysafe products, Polysafe Modena PUR should not have a polish applied.



APPLICATIONS

Polysafe Modena PUR is ideal for use in busy front of house public areas which are normally dry but where there is a risk that water spillage can occur, making slip resistance an important consideration. Typical areas include corridors and circulation areas, receptions, hospital wards, classrooms, shops and cafes as well as social housing applications and normal back of house safety areas.

This includes washrooms, bar serveries and changing rooms. For continually wet areas please refer to our Polysafe Hydro, Hydro Evolve or Ultima ranges.



Polysafe safety flooring ranges have good resistance to dilute acids and alkalis, are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. Chemical resistance charts available on request. For clarification and for information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.

At the date of issue the data presented is correct. However, Polyflor Ltd. reserves the right to make changes which do not adversely affect performance or quality.

* For clarification regarding slip resistance, consult Polyflor.

POLYFLOR LTD. PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
UK SALES DIRECT: +44 (0)161 767 1122 UK SAMPLE REQUESTS: +44 (0)161 767 2551
EXPORT SALES DIRECT: +44 (0)161 767 1913 TECHNICAL SUPPORT: +44 (0)161 767 1912
RECEPTION: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 1128
EXPORT FAX: +44 (0)161 767 1166
E-MAIL: INFO@POLYFLOR.COM WWW.POLYFLOR.COM

James Halstead
FLOORING



2011



Recofloor™
Vinyl Take-Back Scheme



POLYFLOR

**POLYSAFE™
MODENA PUR**



**PERFORMANCE AND
PROPERTIES**



Refer to BRE Global ratings on www.thegreenguide.org.uk



In collaboration with the European Resilient Flooring Manufacturers' Institute (ERFMI), Polyflor Ltd supports sustainable construction via Environmental Product Declarations (EPDs).

