


















Classic Mystique PUR

Attractive, high performance, heavy duty homogeneous floor covering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

- Featuring a non-directional duotone decoration, with marbled tonal highlight chips, Classic Mystique PUR is available in a broad palette of stylish colours.
- Demonstrates outstanding durability and abrasion resistance
- Recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets

	Gauge	ISO 24346 (EN 428)	2mm (0.08")
	Sheet Size	ISO 24341 (EN 426)	2m x 20m = 40m ² (6'6" x 65'6" = 47.84 sq. yards)
	Tile Size	EN 427/ISO 24342	300mm x 300mm = 4.5m ² (11.81" x 11.81" = 5.38 sq. yards) 608mm x 608mm = 5.17m ² (23.94" x 23.94" = 6.18 sq. yards)
	Total Weight	ISO 23997 (EN 430)	3250g/m ² (5.99lbs/sq. yard)
	Responsible Sourcing	BES 6001	Excellent
	General Performance	EN ISO 10581 (EN 649) ASTM F1913 ASTM F1700	Conforms Conforms Class 1, Type A
	Use Area	ISO 10874 (EN 685)	  
	Finish		Polyurethane Reinforced
	Reaction to Fire	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2	Class Bfl-S1 <450 Class 1 FSV < 300; SDV < 500
	Binder Content	EN ISO 10581	Type I
	Flexibility	ASTM F137	Pass
	Bacterial Resistance	ISO 846 Part C	Does not favour growth
	Ease of Radioactive Decontamination	ISO 8690	Excellent
	Slip Resistance	EN 13893 DIN 51130 ASTM D2047	Class DS R9 SCOF ≥ 0.6
	Residual Indentation	ASTM F970 (Modified) ASTM F1914 ISO 24343-1 (EN 433)	≤ 0.005" @ 750psi ≤ 0.005" ≤ 0.10mm
	Impact Sound Reduction	ISO 10140-3	2dB
	Static Electrical Propensity	EN 1815	≤ 2.0kV Classified as 'antistatic'
	Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
	VOC Emissions	Indoor Air Comfort GOLD FloorScore Finnish MI Classification AgBB/ABG	Eurofins certified product Certified Certified Pass
	Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Excellent
	Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 Meets
	Resistance to Light	ASTM F1515	ΔE ≤ 8.0 Meets

Environmentally Preferable Flooring - Polyflor Classic Mystique PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor Classic Mystique PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.ca/sustainability.

PUR - Polyflor Classic Mystique PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

Hygiene - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Agrément Assurance - Polyflor Classic Mystique PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance the appearance and colour will be retained during this period.

Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, email tech@polyflor.ca.

The data presented is correct at the time of printing. For latest information, please visit our website polyflor.ca.
Decoration and shade may vary slightly from the samples shown.

