
















# Pearlazzo PUR

Attractive, high performance, heavy duty homogeneous sheet floorcovering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

Featuring a unique decoration comprising a blend of tonal chips and 4 pearlescent flakes, Pearlazzo PUR is available in a palette of 24 contemporary colours. Demonstrating outstanding durability and abrasion resistance, Pearlazzo PUR is recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets.





	<b>Gauge</b>	EN 428/ISO 24346	2.0mm
	<b>Roll Size</b>	EN 426/ISO 24341	2m x 20m = 40m <sup>2</sup>
	<b>Total Weight</b>	EN 430/ISO 23997	2950g/m <sup>2</sup>
	<b>General Performance</b>	EN 649/EN ISO 10581 ASTM F1913	Conforms Conforms
	<b>Use Area</b>	EN 685/ISO 10874	  
	<b>Reaction to Fire</b>	EN 13501-1 ASTM E662 ASTM E648	Class Bfl-S1 <450 Class 1
	<b>Abrasion Resistance</b>	EN 660-2 EN ISO 10581	Group T Type I
	<b>Slip Resistance</b>	EN 13893 AS 4586 DIN 51130	Class DS R9 R9
	<b>Indentation Residual</b>	ASTM F970 (Modified) ISO 24343-1	Static load 750psi ≤0.1mm
	<b>Electrical behaviour (body voltage)</b>	EN 1815	≤2kV Classified as 'antistatic'
	<b>Castor Chair (continuous use)</b>	EN 425/ISO 4918	Suitable
	<b>VOC Emissions</b>	Indoor Air Comfort GOLD AgBB VOC test Floorscore Finnish M1 Classification Swedish B.P.D (FLEC test) GBCA/NZGBC Green Star IEQ-VOC	Eurofins certified product Pass SCS Certified Reg No: SCS-FS-02034 Pass Best Class Compliant
	<b>Responsible Sourcing</b>	BES 6001	Very Good

**Agrément Assurance** - Polyflor Pearlazzo PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance, the appearance and colour will be retained during this period.

**Environmentally Preferable Flooring** - Polyflor Pearlazzo PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold Plus. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor Pearlazzo PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.com/sustainability](http://www.polyflor.com/sustainability).

**PUR** - Polyflor Pearlazzo PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

 **Hygiene** - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

 Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult **Polyflor Customer Technical Services on +44 (0)161 767 1912, or email [tech@polyflor.com](mailto:tech@polyflor.com)**. The data presented is correct at the time of printing. For latest information, please visit our website [polyflor.com](http://polyflor.com). **Decoration and shade may vary slightly from the samples shown.**

