


CAMARO™ RIGID CORE

Camaro Rigid Core is a collection of high design luxury interlocking vinyl flooring tiles. The rigid (SPC) construction can be laid over most existing floor coverings, significantly reducing installation time and making it a firm favourite with busy, fast paced lifestyles.

Combining an array of realistic wood and stone effect planks and tiles with authentic surface textures, Camaro Rigid Core is ideal for all home interiors.



	Gauge	ISO 24337 (EN 428)	5.5mm
	Wear Layer	ISO 24340 (EN 429)	0.3mm
	IXPE Acoustic Layer		1mm
	Joint Profile		Välinge 5G®
	Plank Size	ISO 24342 (EN 427)	10 @ 177.4 x 1212.4mm = 2.15m ² 24 @ 101.6 x 609.6mm = 1.48m ²
	Tile Size	ISO 24342 (EN 427)	12 @ 304.8 x 609.6mm = 2.22m ²
	Total Weight	ISO 23997 (EN 430)	8570g/m ²
	General Performance	EN 16511	Conforms
	Use Area	ISO 10874 (EN 685)	
	Slip Resistance	EN 13893 DIN 51130	Class DS R10
		For safety flooring with sustainable wet slip resistance, refer to Expona Control or the Polysafe ranges.	
	Abrasion Resistance	EN 15468 Annex A	≥7000 cycles
	Reaction to Fire	EN 13501-1 CAN/ULC S102.2	Class Bfl-S1 FSV < 300; SDV < 500
	Impact Sound Reduction	EN ISO 10140-3	18dB
	Static Electrical Propensity	EN 1815	≤2kV Classified as 'antistatic'
	Residual Indentation	ISO 24343-1 (EN 433)	≤0.1mm
	Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
	Impact Resistance	EN 13329 Annex F	Pass ≥1800mm
	Dimensional Stability	ISO 23999 (EN 434)	≤0.1% Average test value from current production
	Thermal Resistance	EN 12664	0.0356 m ² K/W Suitable for underfloor heating. Max 27°C
	Light Fastness	ISO 105-B02	(Method 3) >6
	Furniture Leg	ISO 16581 (EN 424)	Pass (no visible damage) Foot type O
	Swelling	ISO 24336	Pass (0.0%)
	Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance - Resistant depending on concentration and time of exposure. In case of increased impact of oils, grease, acids, alkalis and other aggressive chemicals, please contact us.
	VOC Emissions	Indoor Air Comfort GOLD FloorScore AgBB VOC test	Eurofins certified product Certified Very low emissions
	Responsible Sourcing	SA 8000	Approved factory
	Environmentally Preferable Flooring - It is 100% recyclable and contains average 15% recycled material. Recyclable via the Recofloor scheme. Visit www.polyflor.com/sustainability		
	PUR - Polyflor Camaro Rigid Core features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.		
	For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com . The data presented is correct at the time of printing. For latest information, please visit our website polyflor.com . Decoration and shade may vary slightly from the samples shown.		



Polyflor Inc. North American Headquarters, 3209 Orlando Drive, Mississauga, Ontario L4V 1C5 | Phone: 1 905 364 3000 | www.polyflor.ca
For general enquiries contact info@polyflor.ca; office hours Monday - Friday, 08:30 to 17:30 EST

