

















# Pearlazzo PUR


Attractive, high performance, heavy duty homogeneous sheet floor covering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

- Featuring a unique decoration comprising a blend of tonal chips and 4 pearlescent flakes, Pearlazzo PUR is available in a palette of 24 contemporary colours.
- Demonstrates outstanding durability and abrasion resistance
- Recommended for use throughout commercial interiors, healthcare and education facilities, as well as retail outlets


	<b>Gauge</b>	ISO 24346 (EN 428)	2mm (0.08")
	<b>Sheet Size</b>	ISO 24341 (EN 426)	2m x 20m = 40m <sup>2</sup> (6'6" x 65'6" = 47.84 sq. yards)
	<b>Total Weight</b>	ISO 23997 (EN 430)	2950g/m <sup>2</sup> (5.44lbs/sq. yard)
	<b>Responsible Sourcing</b>	BES 6001	Excellent
	<b>General Performance</b>	EN ISO 10581 (EN 649) ASTM F1913	Conforms Conforms
	<b>Use Area</b>	ISO 10874 (EN 685)	
	<b>Finish</b>		Polyurethane Reinforced
	<b>Reaction to Fire</b>	EN 13501-1 ASTM E662 ASTM E648 CAN/ULC S102.2	Class Bfl-S1 <450 Class 1 FSV < 300; SDV < 500
	<b>Abrasion Resistance</b>	EN 660-2	Group T
	<b>Binder Content</b>	EN ISO 10581	Type I
	<b>Flexibility</b>	ASTM F137	Pass
	<b>Bacterial Resistance</b>	ISO 846 Part C	Does not favour growth
	<b>Ease of Radioactive Decontamination</b>	ISO 8690	Excellent
	<b>Slip Resistance</b>	EN 13893 DIN 51130 ASTM D2047	Class DS R9 SCOF ≥ 0.6
	<b>Residual Indentation</b>	ASTM F970 (Modified) ASTM F1914 ISO 24343-1 (EN 433)	≤ 0.005" @ 750psi ≤ 0.005" ≤ 0.10mm
	<b>Impact Sound Reduction</b>	ISO 10140-3	2dB
	<b>Static Electrical Propensity</b>	EN 1815	≤ 2.0kV Classified as 'antistatic'
	<b>Castor Chair (continuous use)</b>	ISO 4918 (EN 425)	Suitable
	<b>VOC Emissions</b>	Indoor Air Comfort GOLD FloorScore Finnish M1 Classification AgBB/ABG	Eurofins certified product Certified Certified Pass
	<b>Resistance to Chemicals</b>	ISO 26987 (EN 423) ASTM F925	Good resistance Excellent
	<b>Resistance to Heat</b>	ASTM F1514	ΔE ≤ 8.0 Meets
	<b>Resistance to Light</b>	ASTM F1515	ΔE ≤ 8.0 Meets

**Environmentally Preferable Flooring** - Polyflor Pearlazzo PUR achieves a BRE Global Environmental A+ Rating (Certificate No: ENP 472) in major use areas such as education and healthcare and is GreenTag LCA Rate certified with GreenRate level A - Gold. Generic EN 15804 Environmental Product Declaration (EPD) available on request. Polyflor Pearlazzo PUR is 100% recyclable and contains 25% recycled material. Recyclable via the Recofloor scheme. Visit [www.polyflor.ca/sustainability](http://www.polyflor.ca/sustainability).

**PUR** - Polyflor Pearlazzo PUR features a high quality, cross-linked polyurethane reinforcement, UV cured to provide a low-cost, polish free maintenance regime for the lifetime of the flooring.

 **Hygiene** - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

**Agrément Assurance** - Polyflor Pearlazzo PUR has been independently assessed by the British Board of Agrément and product performance is assured for at least 10 years in recommended use areas. With proper maintenance the appearance and colour will be retained during this period.

 Polyflor homogeneous PUR ranges are compatible for use with the most commonly used alco-based hand gels and are suitable for steam cleaning on a periodic basis. For information regarding handling and installation, adhesives, maintenance, applications, chemical resistance and product warranty, email [tech@polyflor.ca](mailto:tech@polyflor.ca).

The data presented is correct at the time of printing. For latest information, please visit our website [polyflor.ca](http://polyflor.ca).  
**Decoration and shade may vary slightly from the samples shown.**

