

# SPORT67


High performance, heavy duty, multi-use sports floor covering with a polyurethane reinforcement for low cost, lifetime polish free maintenance.

Polyflor Sport 67 is recommended for use in school and local authority sports halls, gymnasias and leisure centres, where resilience underfoot and long life under heavy traffic are needed. Polyflor Sport 67 meets Sport England and Sport Scotland requirements and is a multi-use sports floor for general sporting activities including football, netball, basketball, volleyball, tennis and badminton.



	<b>Gauge</b>	-	6.7mm
	<b>Roll Size</b>	-	2m x 18.5m = 37m <sup>2</sup>
	<b>Total Weight</b>		3600g/m <sup>2</sup>
	<b>General Performance</b>	EN 14904 ASTM F2772	Meets Conforms
	<b>Sliding Coefficient of Friction</b>	EN 13036	80 - 110
	<b>Shock Absorption</b>	EN 14808	Pass
	<b>Ball Rebound</b>	EN 12235	Pass
	<b>Vertical Deformation</b>	EN 14809	Pass
	<b>Reaction to Fire</b>	EN 13501-1	Class Cfl-S1
	<b>Abrasion Resistance</b>	EN 649 EN ISO 5470-1	Group T <1000mg
	<b>Impact Resistance</b>	EN 1517	Pass
	<b>Resistance to Indentation</b>	EN 1516	Pass
	<b>Specular Gloss</b>	ISO 2813	≤30%
	<b>Rolling-Load Resistance</b>	EN 1569	Pass
	Polyflor Sport 67 is reinforced with polyurethane for improved cleaning and maintenance. Polyflor Sport 67 should not have a polish applied.		
	<b>VOC Emissions</b>	FloorScore	Certified
	Environmentally Preferable Flooring - 100% recyclable. Recyclable via the Recofloor scheme. Contains 24% recycled content.		
	<b>Hygiene</b> - All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
	For information regarding handling and installation (including line marking), adhesives, maintenance, applications and chemical resistance, consult Polyflor Customer Technical Services on +44 (0)161 767 1912, or email tech@polyflor.com.		

<b>LINE MARKINGS</b> (width and colours)					
	50mm	40mm	50mm	50mm	50mm



BS EN 14041 EN 14904



Polyflor Inc. North American Headquarters, 3209 Orlando Drive, Mississauga, Ontario L4V 1C5 | Phone: 1905 364 3000 | www.polyflor.ca  
For general enquiries contact info@polyflor.ca; office hours Monday - Friday, 08:30 to 17:30 EST

