

Expona Simplay 19dB PUR



PRODUCT SPECIFICATION

Key Features

- > Wood & stone designs
- > Acoustic loose lay planks & tiles in multiple sizes
- > Can be installed over existing floor coverings
- > In-built IXPE acoustic backing
- > Up to 19dB impact sound reduction
- > Heavy commercial applications & residential



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	5.0mm
Wear Layer	ISO 24340 (EN 429)	0.55mm
Total Weight	ISO 23997 (EN 430)	6380g/m ²
Finish		PUR

Plank & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	177.8mm x 1219.2mm	8	10	2.17m ²
Tile	600mm x 600mm	4	6	2.16m ²

Performance Requirements	Standard	Result
General Performance	ISO 11638 (EN 651)	Conforms
Use Area	ISO 10874 (EN 685)	23, 33, 42
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2	Class Cfl-S1 Class 1 >4.5 kW/m ² FSV < 300; SDV < 500
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970 ASTM F1914	≤0.20mm* ≤0.018" @ 750psi ≤0.019"
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434) ASTM F2199	≤0.25% Pass
Flexibility	ASTM F137	1" - Pass
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6

Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$ - Meets
Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$ - Meets

*Average test value from current production.

Sustainability

Standard	Result
BRE Green Guide	A+ Generic
Recyclable & Reusable	100%
Recycled Content	17%
REACH	Compliant
Indoor Air Comfort Gold	Eurofins certified product
FloorScore	Certified
AgBB/ABG	Pass

Acoustic Performance

Standard	Result
Impact Sound Reduction	ISO 10140-3 19dB
Sound Transmission Coefficient	ASTM E90/492 STC 55
Impact Insulation Class	ASTM E90/492 IIC 56
IXPE Acoustic Layer	1.0mm

Maintenance Performance

Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925 Good resistance Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



BS EN 14041

EN 14041

Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1

Expona Simplay 19dB PUR

RANGE SHADES



177.8mm x 1219.2mm
7" x 48"



White Rustic Pine **9067**  LRV 41



Grey Country Oak **9063**  LRV 40



Natural Rustic Pine **9068**  LRV 22



Blond Country Oak **9064**  LRV 36



American Oak **9062**  LRV 34



Light Cherry **9061**  LRV 26




Natural Ash **9065**  LRV 22



Grey Ash **9066**  LRV 28

600mm x 600mm
23.6" x 23.6"




Cold Grey Concrete **9069** 
LRV 18



Warm Grey Concrete **9071** 
LRV 23



Light Grey Concrete **9070** 
LRV 34



Dark Grey Concrete **9072** 
LRV 13

LRV - Light Reflectance Value

 Bevelled Edges

 Colour/Pattern Variation