

# Forest fx PUR

## PRODUCT SPECIFICATION

### Key Features

- > Collection of wood designs in vinyl sheet format
- > Contemporary parquet designs
- > BRE Green Guide certified
- > Low cost, polish-free maintenance
- > Commercial interiors



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.70mm
Total Weight	ISO 23997 (EN 430)	2660g/m <sup>2</sup>
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	18	-	40m <sup>2</sup>

Performance Requirements	Standard	Result
General Performance	ISO 10582 (EN 649) ASTM F1303	Conforms Type I, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 ASTM D2047	Class DS R10 R10 SCOF ≥0,5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2	Class Bfl-S1 Class 1 FSV < 300; SDV < 500
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F1914 ASTM F970 (Modified) ISO 24343-1	<0.005" <0.005" (750psi) ≤0.10mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
Flexibility	ISO 24344 (EN 435) ASTM F137	(Method A) Pass 20mm ø 0.25" Pass
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6

Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$ - Meets
Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$ - Meets

## Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 415
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

## Acoustic Performance

	Standard	Result
Impact Sound Reduction	ISO 10140-3	8dB

## Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

## Hygiene

	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth



BS EN 14041



EN 14041

### Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

# Forest fx PUR

## RANGE SHADES



**Parish Oak Parquet 3106**  
plank size in sheet: 76.2 x 288.6mm  
w/r 9841 LRV 32



**Blanched Oak 3113**  
plank size in sheet: 200 x 1000mm  
w/r 3113 LRV 42



**Oslo Oak 3104**  
plank size in sheet: 167 x 1500mm  
w/r 9829 LRV 32



**Newport Oak 3109**  
plank size in sheet: 167 x 1500mm  
w/r 9838 LRV 30



**Grey Sawmill Oak 3101**  
plank size in sheet: 180 x 1000mm  
w/r 3101 LRV 40



**Rock Salt Oak 3103**  
plank size in sheet: 220 x 1500mm  
w/r 3103 LRV 37



**Alloyed Timber 3105**  
plank size in sheet: 167 x 1500mm  
w/r 9841 LRV 24



**Oiled Oak 2990**  
plank size in sheet: 167 x 1500mm  
w/r 2990 LRV 35



**Rural Deckwood 3102**  
plank size in sheet: 180 x 1000mm  
w/r 3102 LRV 28



**Eton Oak Parquet 3108**  
plank size in sheet: 76.2 x 288.6mm  
w/r 9822 LRV 24



**Classic Oak 3100**  
plank size in sheet: 167 x 1500mm  
w/r 3330 LRV 29



**Rustic Oak 3330**  
plank size in sheet: 84 x 332/664mm  
w/r 3330 LRV 29



**American Oak 3380**  
plank size in sheet: 100 x 1000mm  
w/r 3380 LRV 36



**European Oak 3340**  
plank size in sheet: 100 x 1000mm  
w/r 3340 LRV 21




**French Walnut 3120**  
plank size in sheet: 167 x 1000mm  
w/r 3120 LRV 17



**Smoked Oak 3150**  
plank size in sheet: 167 x 1500mm  
w/r 3150 LRV 14



**Mahogany 3360**  
plank size in sheet: 84 x 332/664mm  
w/r 3360 LRV 10



**Brazilian Walnut 3990**  
plank size in sheet: 133 x 1000mm  
w/r 3990 LRV 8

w/r - Weld Rod

LRV - Light Reflectance Value

### Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1