

Polysafe Stone fx PUR



PRODUCT SPECIFICATION

Key Features

- > Safety flooring in high clarity stone & concrete designs
- > Virtually invisible aluminium oxide particles
- > Pendulum test - 36+ (slider 96)
- > Sustainable slip resistance vinyl flooring
- > Suitable for heavy commercial use, like receptions, hospital wards and bars



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.70mm
Total Weight	ISO 23997 (EN 430)	2780g/m ²
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	22	-	40m ²

Performance Requirements	Standard	Result
General Performance	EN 13845 ASTM F1303	Conforms Conforms
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845 RRL Pendulum Test DIN 51130 / DIN EN 16165 Ann. B Surface Roughness ASTM D2047	ESf ≥36 (wet test - 4S Rubber / Slider 96) R10 Rz ≥20µm SCOF ≥0.8
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2 AS ISO 9239-1	Class Bfl-S1 Class 1 FSV < 300; SDV < 500 >8.0kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750psi)
Flexibility	ASTM F137	1.5" Pass
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability

	Standard	Result
BRE Green Guide		A+ ENP 415
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Maintenance Performance

	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.

Hygiene

	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth



Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca


© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1


Polysafe Stone fx PUR




RANGE SHADES




Dove Slate **6012** w/r 6012
NCS S 3502-G LRV 35



Urban Concrete **6013** w/r 6013
NCS S 5502-Y LRV 24




Jurassic Stone **6011** w/r 6011
NCS S 4500-N LRV 22




Natural Slate **6014** w/r 6014
NCS S 4502-G LRV 22



Dark Concrete **5089** w/r 5089
NCS S 5502-Y LRV 23



Flagstone Grey **5091** w/r 5091
NCS S 4005-Y50R LRV 35



Clay Stone **5092** w/r 5092
NCS S 5005-Y80R LRV 25



Light Concrete **5087** w/r 5087
NCS S 4005-G80Y LRV 33



Deep Fossil **5082** w/r 5082
NCS S 5502-Y LRV 22



Pebble Grey **5083** w/r 5083
NCS S 4000-N LRV 34



Muted Stone **5081** w/r 5081
NCS S 2005-Y50R LRV 46



Grey Flourite **4042** w/r 9803
NCS S 2002-Y50R LRV 48



Agate Grey **4043** w/r 9804
NCS S 3500-N LRV 38



Galena **4047** w/r 9807
NCS S 4502-R LRV 27




Gypsum **4044** w/r 9800
NCS S 2005-Y30R LRV 50



Copal **4046** w/r 9801
NCS S 3010-Y20R LRV 39



Andesite **4049** w/r 9802
NCS S 4005-Y50R LRV 26



Angelite **4051** w/r 9806
NCS S 3010-R90B LRV 40




Blue Quartz **4054** w/r 9808
NCS S 6010-R90B LRV 17



Jetstone **4045** w/r 9805
NCS S 6500-N LRV 15



Pearl River **5084** w/r 5084
NCS S 1000-N LRV 63



Valley Rock **5086** w/r 5086
NCS S 7005-Y20R LRV 14

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System

Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

V1