

Polysafe Wood fx Acoustix PUR



PRODUCT SPECIFICATION

Key Features

- > High clarity wood effect safety vinyl flooring
- > Impact Sound Reduction of 19dB
- > Pendulum test - 36+ (slider 96)
- > Sustainable slip resistant safety flooring
- > Polysafe PUR for superior cleaning benefits



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	3.7mm
Wear Layer	ISO 24340 (EN 429)	0.65mm
Total Weight	ISO 23997 (EN 430)	2670g/m ²
Finish		PUR

Sheet Size	Size	Shades	Quantity per Box	Coverage per Box/Roll
Sheet	2m x 20m	8	-	40m ²

Performance Requirements	Standard	Result
General Performance	ISO 11638 (EN 651)	Conforms
Use Area	ISO 10874 (EN 685)	23, 34, 42
Enhanced Slip Resistance	EN 13845 AS 4586 RRL Pendulum Test Surface Roughness	ESf R10 ≥36 (wet test - 4S Rubber / Slider 96) Rz ≥20µm
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2	Class Bfl-S1 Class 1 FSV < 300; SDV < 500
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ISO 24343-1	≤0.20mm

Sustainability	Standard	Result
BRE Green Guide		A+ ENP 415
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product

FloorScore		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance	Standard	Result
Impact Sound Reduction	ISO 10140-3	19dB

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.



Polysafe Wood fx Acoustix PUR



RANGE SHADES

PARQUET DESIGNS



Eton Oak Parquet 3399
plank size in sheet: 76.2 x 288.6mm
w/r 9822 LRV 24



Parish Oak Parquet 3398
plank size in sheet: 76.2 x 288.6mm
w/r 9841 LRV 32



American Oak 3382
plank size in sheet: 100 x 1000mm
w/r 3380 LRV 37



Sun Bleached Oak 3384
plank size in sheet: 200 x 1500mm
w/r 3372 LRV 31



Rustic Oak 3332
plank size in sheet: 83 x 333/666mm
w/r 3330 LRV 26



Silver Oak 3352
plank size in sheet: 83 x 333/666mm
w/r 3237 LRV 23



European Oak 3342
plank size in sheet: 100 x 1000mm
w/r 3340 LRV 23



Aged Oak 3389
plank size in sheet: 200 x 1500mm
w/r 9824 LRV 9

w/r - Weld Rod

LRV - Light Reflectance Value

Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.