

APEX

APEX

Polysafe Apex is a safety vinyl flooring range combining the assurance of sustainable wet slip resistance with high durability for years of performance in extreme, heavy footfall commercial areas.

Particularly suitable in busy kitchen environments whether commercial, gourmet or food preparation areas where over 100 meals are served daily and the floor is subjected to everyday spillages.

- Safety sheet flooring available in 6 colours
- R12 slip resistance per standard
 DIN 51130
- Approved for the use area classification 23, 34, 43





Technical Specification

Product Format

Gauge	ISO 24346 (EN 428)	2.5mm	
Total Weight	ISO 23997 (EN 430)	3150g/m ²	
Performance Requir			
	EN 13845	Conforms	
General Performance	ASTM F1303	Type II, Grade I, Class B	
		Backing	
Use Area	ISO 10874 (EN 685)	23, 34, 43	
	EN 13845	ESf	
	AS 4586	R12	
Enhanced Slin	RRL Pendulum Test ≥45 (wet test -		
Enhanced Slip Resistance		4S Rubber / Slider 96)	
	DIN 51130 / R12		
	DIN EN 16165 Ann. B		
	UNE-ENV 12633	Class 3 (Slider 96)	
Abrasion Resistance	EN 13845	50,000 cycles	
	EN 13501-1	Class BfI-S1	
Reaction to Fire	ASTM E648	Class 1	
	CAN/ULC S102.2	FSV < 300; SDV < 500	
	AS ISO 9239-1	>8.0kW/m ²	
Static Electrical	EN 1815	≤2.0kV Classified as	
Propensity	CIOI NI	'antistatic'	
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750 psi)	
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets	

Sheet Size

Format	Size	Shades	Coverage per Roll
Sheet	2m x 20m	6	40m²
	(2.187 yds x 21.872 yds)		(47.834 yds)

Sustainability

BRE Green Guide		A+ ENP 472
GreenTag	LCA Rate Silver Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		Contains recycled material
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Maintenance Performance

Di-t	Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	Resistance to Chemicals	ASTM F925	Good resistance
	Alco Hand Gels	Compatible for use with most commonly used	
AICO Hand Geis	alco-based hand gels		
	Steam Cleaning	Suitable for steam cleaning on a periodic basis	


All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence $\,$


Hygiene


Bacterial Resistance ISO 846 Part C Does not favour growth	Bacterial Resistance	ISO 846 Part C	Does not favour growth
--	----------------------	----------------	------------------------


Polysafe Apex














NCS S 5010-R90B

NCS S 5005-Y80R

LRV 18

LRV 23 NCS S 6500-N

LRV 15



NCS S 8000-N

w/r - Weld Rod	LRV - Light Reflectance Value	NCS - Natural Colour System

APEX









Let us help you

Our history

Founded in 1915, James Halstead plc, the parent company of Polyflor Ltd, was originally a textile company based in Manchester, UK, until the 1950's when it pioneered the development of homogeneous vinyl floorings.



Responsible sourcing

Polyflor is proud to be the first flooring manufacturer to be awarded BES 6001 certification for the Responsible Sourcing of Construction Product, achieving an Excellent rating. This is a recognised standard certified by BRE Global which proves that a manufacturer is using materials that have been responsibly sourced and acts responsibly.



Help is here

Polyflor has dedicated and experienced personnel within its sales, marketing, technical and design departments, to provide comprehensive support to our customers. We are ready to assist with queries on topics such as product selection specification, installation, performance an ongoing maintenance.




Product innovation

In collaboration with industry partners, Polyflor is working on developments in new products and technologies. Recent launches include a non-directional homogeneous sheet collection that keeps waste to a minimum and loose lay adhesive-free safety sheet and high design tile and plank flooring for quick turnaround projects.



Design service

and advise colours and product choices when you're looking to create a memorable floor design. We offer the precision and the flexibility of waterjet cutting to



BIM objects

A selection of Polyflor's market leading product ranges are now available as Building Information Modelling (BIM) objects.

These objects can be downloaded free of charge from the NBS National BIM Library or www.polyflor.com/bim and www.bimobject.com

Commitment to our supply chain

With ISO 9001 Quality Management and ISO 14001 accreditation, the availability of consistent, good quality products is ensured. We test our products to a wide range of international standards, including slip resistance and VOC emissions, to back-up their performance.



Flooring when you need it

Thanks to Polyflor's extensive warehousing facilities and commitment to holding large quantities of stock, we can react quickly to orders and offer faster lead times for our customers. Polyflor products are readily available worldwide through our wide network of supporting agents and wholesale partners.



Training at Polyflor

To encourage best practice throughout the flooring sector, Polyflor offers both floor laying and floor cleaning courses in a purpose-built facility. For more info contact info@polyflor.ca







Recycling vinyl

Polyflor is a co-founding and funding member of Recofloor, the UK flooring industry's leading vinyl take back scheme for waste vinyl off-cuts and smooth uplifted flooring. For more information about the Recofloor recycling scheme visit www.recofloor.org



Low maintenance

Polyflor's PUR polyurethane reinforcement is cross linked and UV cured for enhanced protection, optimum appearance retention and superior cleaning benefits such as an easier more environmentally friendly maintenance regime. For further in-depth and tailored information on floor maintenance, visit www.polyflor.ca



Free samples

o request free individual product amples of any of Polyflor's flooring ollections, visit www.polyflor.ca or mail us at samples@polyflor.ca .lternatively, you can call the edicated Polyflor Sample Hotline n (905) 364-3000

8



POLYFLOR TM INTERNATIONAL

Australia Polyflor Australia Tel: 1800 777 425

Email: sales@polyflor.com.au

Canada Polyflor Canada Inc. Tel: +1 905 364 3000 Email: sales@polyflor.ca

China Polyflor Hong Kong O/B Polyflor Ltd. Tel: +(852) 2865 0101 Email: info@polyflor.com.hk

Colombia Polyflor Ltd. (LATAM Office) Tel: +57 3223082375 Email: info@polyflor.com

France James Halstead France SAS Tel: +33 (0)8 20 20 32 11 Email: info@jhfrance.fr

Germany objectflor Art und Design Belags GmbH Tel: +49 (0) 2236 966 330 Email: info@objectflor.de

India Polyflor India Pvt Ltd. Tel: +91 22 4023 2485 Tel: +91 22 4023 2486 Email: info@polyflor.co.in Ireland Polyflor Ireland Tel: +353 (1) 864 9304 Email: salesireland@polyflor.com

Malaysia Polyflor Martex Tel: 1300 80 7788 Email: sales@polyflor.com.my

Middle East Polyflor FZE Tel: +971 50 406 8114 E-mail: aelwakil@polyflorfze.ae

New Zealand Polyflor New Zealand Ltd. Tel: 0800 765 935 Tel: +64 9 269 1111 Email: sales@polyflor.co.nz

Norway Polyflor Nordic Tel: +47 23 00 84 00 Email: firmapost@polyflor.no

Spain Polyflor Ltd. Tel: +34 619 949 054 Email: info@polyflor.com

Sweden Polyflor Nordic Sweden AB Tel: +46 (0) 300 15820 Email: info@polyflor.se

POLYFLOR CANADA INC.

3209 Orlando Dr, Mississauga Ontario L4V 1C5, Canada

Tel: (905) 364-3000 E-mail: sales@polyflor.ca

James Halstend"
FLOORING