



SILENTFLOR PUR

SILENTFLOR PUR

Elegantly combining contemporary and decorative design with superior acoustic performance, the Silentflor vinyl sheet flooring range has been expertly created for a wide range of commercial interiors.

Silentflor provides a perfect solution for installations in the healthcare, office, education, residential, retail and leisure sectors. An environmentally preferable flooring collection, Silentflor is also 100% recyclable.

- Acoustic sheet flooring available in 36 colours
- PUR no wax, no finish, low maintenance
- Impact sound reduction level of 19dB





Silentflor PUR

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	3.7mm
Wear Layer	ISO 24340 (EN 429)	0.65mm
Total Weight	ISO 23997 (EN 430)	2550g/m ²
Finish	PUR	
Performance Requirements		
General Performance	ISO 11638 (EN 651)	Conforms
	ASTM F1303	Type I, Class I, Class C Backing
Use Area	ISO 10874 (EN 685)	23, 34, 42
Slip Resistance	EN 13893	Class DS
	DIN 51130 /	R10
	DIN EN 16165 Ann. B	
	AS 4586	R10
	ASTM D2047	SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 651	Group T
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1
	CAN/ULC S102.2	FSV < 300; SDV < 500
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F1914	≤0.005"
	ASTM F970 (Modified)	≤0.009" (750 psi)
	ISO 24343-1	≤0.20mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434)	≤0.40%
Flexibility	ISO 24344 (EN 435)	(Method A) Pass 20mm ø
	ASTM F137	0.25" Pass
Thermal Resistance	EN 12667	0.0525m ² K/W
Underfloor Heating	Suitable, max 27°C	
Light Fastness	ISO 105-B02 (Method 3)	≥6
Furniture Leg	ISO 16581 (EN 424)	Pass
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sheet Size

Format	Size	Shades	Coverage per Roll
Sheet	2m x 20m (2.187 yds x 21.872 yds)	36	40m ² (47.834 yds)

Sustainability		
BRE Green Guide		A+ ENP 415
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD	Available	
Recyclable	100%	
Recycled Content	10%	
REACH	Compliant	
Indoor Air Comfort Gold	Eurofins certified product	
FloorScore	Certified	
Finnish M1 Classification	Certified	
AgBB/ABG	Pass	
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance		
Impact Sound Reduction	ISO 10140-3	19dB
Sound Transmission Coefficient	ASTM E90/492	STC 56
Impact Insulation Class	ASTM E90/492	IIC 57

Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		

Silentflor PUR



Warm Limed Ash 9953
plank size in sheet: 166 x 1500mm
w/r 9832 LRV 34



Classic Limed Ash 9955
plank size in sheet: 166 x 1500mm
w/r 9833 LRV 49



Sun Bleached Oak 9952
plank size in sheet: 200 x 1500mm
w/r 9825 LRV 31



Blond Oak 9956
plank size in sheet: 167 x 1500mm
w/r 9820 LRV 28



Roasted Limed Ash 9954
plank size in sheet: 166 x 1500mm
w/r 9831 LRV 27




English Oak 9957
plank size in sheet: 200 x 1500mm
w/r 9823 LRV 24



Honey Oak 9959
plank size in sheet: 167 x 1500mm
w/r 9821 LRV 22



Toasted Oak 9960
plank size in sheet: 167 x 1500mm
w/r 9822 LRV 18



Reclaimed Chevron 9958
plank size in sheet: 120 x 700mm
w/r 9830 LRV 17



Bronzed Pine 9962
plank size in sheet: 166 x 1500mm
w/r 9835 LRV 14



Aged Oak 9961
plank size in sheet: 200 x 1500mm
w/r 9824 LRV 8



Smoked Oak 9963
plank size in sheet: 200 x 1500mm
w/r 9827 LRV 11



Silver Oak 9951
plank size in sheet: 200 x 1500mm
w/r 9826 LRV 28



Silvered Pine 9964
plank size in sheet: 166 x 1500mm
w/r 9836 LRV 17



Honey Beige 9985
NCS S 3005-Y50R
w/r 9869 LRV 29




Autumn Rain 9986
NCS S 5005-Y80R
w/r 9864 LRV 24

Silentflor PUR




Burnt Orange 9981
NCS S 3040-Y40R
w/r 9848 LRV 24




Flaxen 9979
NCS S 0560-Y
w/r 9849 LRV 44




Meadow 9980
NCS S 2050-G90Y
w/r 9850 LRV 32



Teal 9978
NCS S 6020-B70G
w/r 9851 LRV 11



Steel Blue 9977
NCS S 6020-B10G
w/r 9852 LRV 10




Moleskin 9975
NCS S 3005-Y20R
w/r 9841 LRV 28



Storm 9973
NCS S 3502-B
w/r 9845 LRV 26



Taupe 9976
NCS S 7502-Y
w/r 9843 LRV 10



Jet 9974
NCS S 8000-N
w/r 9842 LRV 8



Zinc 9982
NCS S 3500-N
w/r 9804 LRV 37



Onyx 9983
NCS S 7502-R
w/r 9805 LRV 14



Twilight 9984
NCS S 7005-Y20R
w/r 5086 LRV 14



Light Grey Concrete 9965
NCS S 3000-N
w/r 9858 LRV 40



Warm Concrete 9967
NCS S 3502-R
w/r 9855 LRV 25



Cool Concrete 9966
NCS S 4500-N
w/r 9856 LRV 22



Dark Grey Concrete 9968
NCS S 6502-R
w/r 9857 LRV 13



Light Industrial Concrete 9969
NCS S 2500-N
w/r 9860 LRV 35



Dark Industrial Concrete 9970
NCS S 4502-R
w/r 9859 LRV 24



Copper Ornamental 9971
NCS S 5502-R
w/r 9861 LRV 19



Onyx Ornamental 9972
NCS S 7000-N
w/r 9862 LRV 11

SilentflorPUR





Cool Concrete 9966



Smoked Oak 9963



Silvered Pine 9964



Zinc 9982

All you need to know

Our history

Founded in 1915, James Halstead plc, the parent company of Polyflor Ltd, was originally a textile company based in Manchester, UK, until the 1950's when it pioneered the development of homogeneous vinyl floorings.



Responsible sourcing

Polyflor is proud to be the first flooring manufacturer to be awarded BES 6001 certification for the Responsible Sourcing of Construction Product, achieving an Excellent rating. This is a recognised standard certified by BRE Global which proves that a manufacturer is using materials that have been responsibly sourced and acts responsibly.




Help is here

Polyflor has dedicated and experienced personnel within its sales, marketing, technical and design departments, to provide comprehensive support to our customers. We are ready to assist with queries on topics such as product selection, specification, installation, performance and ongoing maintenance.




BIM objects

A selection of Polyflor's market leading product ranges are now available as Building Information Modelling (BIM) objects. These objects can be downloaded free of charge from the NBS National BIM Library or www.polyflor.com/bim and www.bimobject.com



Product innovation

In collaboration with industry partners, Polyflor is working on developments in new products and technologies. Recent launches include a non-directional homogeneous sheet collection that keeps waste to a minimum and loose lay adhesive-free safety sheet and high design tile and plank flooring for quick turnaround projects.



Design service

Our designers can provide visuals and advise colours and product choices when you're looking to create a memorable floor design. We offer the precision and the flexibility of waterjet cutting to produce any design you require.

Commitment to our supply chain

With ISO 9001 Quality Management and ISO 14001 accreditation, the availability of consistent, good quality products is ensured. We test our products to a wide range of international standards, including slip resistance and VOC emissions, to back-up their performance.



Flooring when you need it

Thanks to Polyflor's extensive warehousing facilities and commitment to holding large quantities of stock, we can react quickly to orders and offer faster lead times for our customers. Polyflor products are readily available worldwide through our wide network of supporting agents and wholesale partners.



Training at Polyflor

To encourage best practice throughout the flooring sector, Polyflor offers both floor laying and floor cleaning courses in a purpose-built facility. For more info contact info@polyflor.ca



Recycling vinyl

Polyflor is a co-founding and funding member of Recofloor, the UK flooring industry's leading vinyl take back scheme for waste vinyl off-cuts and smooth uplifted flooring. For more information about the Recofloor recycling scheme visit www.recofloor.org



Low maintenance

Polyflor's PUR polyurethane reinforcement is cross linked and UV cured for enhanced protection, optimum appearance retention and superior cleaning benefits such as an easier more environmentally friendly maintenance regime. For further in-depth and tailored information on floor maintenance, visit www.polyflor.ca



Free samples

To request free individual product samples of any of Polyflor's flooring collections, visit www.polyflor.ca or email us at samples@polyflor.ca. Alternatively, you can call the dedicated Polyflor Sample Hotline on (905) 364-3000





Zinc 9982



Steel Blue 9977

POLYFLORTM INTERNATIONAL

Australia
Polyflor Australia
Tel: 1800 777 425
Email: sales@polyflor.com.au

Canada
Polyflor Canada Inc.
Tel: +1 905 364 3000
Email: sales@polyflor.ca

China
Polyflor Hong Kong O/B Polyflor Ltd.
Tel: +(852) 2865 0101
Email: info@polyflor.com.hk

Colombia
Polyflor Ltd. (LATAM Office)
Tel: +57 3223082375
Email: info@polyflor.com

France
James Halstead France SAS
Tel: +33 (0)8 20 20 32 11
Email: info@jhfrance.fr

Germany
objectflor Art und Design Belags GmbH
Tel: +49 (0) 2236 966 330
Email: info@objectflor.de

India
Polyflor India Pvt Ltd.
Tel: +91 22 4023 2485
Tel: +91 22 4023 2486
Email: info@polyflor.co.in

Ireland
Polyflor Ireland
Tel: +353 (1) 864 9304
Email: salesireland@polyflor.com

Malaysia
Polyflor Martex
Tel: 1300 80 7788
Email: sales@polyflor.com.my

Middle East
Polyflor FZE
Tel: +971 50 406 8114
E-mail: aelwakil@polyflorfze.ae

New Zealand
Polyflor New Zealand Ltd.
Tel: 0800 765 935
Tel: +64 9 269 1111
Email: sales@polyflor.co.nz

Norway
Polyflor Nordic
Tel: +47 23 00 84 00
Email: firmapost@polyflor.no

Spain
Polyflor Ltd.
Tel: +34 619 949 054
Email: info@polyflor.com

Sweden
Polyflor Nordic Sweden AB
Tel: +46 (0) 300 15820
Email: info@polyflor.se

POLYFLOR CANADA

3209 Orlando Dr, Mississauga Ontario
L4V 1C5, Canada

Tel: (905) 364-3000
E-mail: sales@polyflor.ca

www.polyflor.ca

*James Halstead*TM
FLOORING