

MOSAIC PUR

MOSAIC PUR

Polysafe Mosaic PUR is a high specification, decorative safety vinyl flooring range combining the assurance of sustainable slip resistance with high durability for years of performance.

Ideally suited for heavy traffic areas
where there are risks of water spillage
and other contaminants in
commercial and residential areas such
as corridors, receptions, hospital wards,
classrooms, shops, and bars & cafes.

- Safety sheet flooring available in 10 colours
- PUR no wax, no finish, low maintenance
- R10 slip resistance per standard DIN
 51130





Technical Specification

Product Format

| Gauge | ISO 24346 (EN 428) | 2.0mm |
|--------------|--------------------|----------------------|
| Wear Layer | ISO 24340 (EN 429) | 0.70mm |
| Total Weight | ISO 23997 (EN 430) | 2400g/m ² |
| Finish | | PUR |

| Performance Requ | irements | |
|---------------------|---------------------|------------------------|
| General Performance | EN13845 | Conforms |
| | ASTM F1303 | Conforms |
| Use Area | ISO 10874 (EN 685) | 23, 34, 43 |
| | EN 13845 | ESf |
| | AS 4586 | R10 |
| | RRL Pendulum Test | ≥36 (wet test - |
| Enhanced | | 4S Rubber / Slider 96) |
| Slip Resistance | DIN 51130 / | R10 |
| | DIN EN 16165 Ann. B | |
| | Surface Roughness | Rz ≥20μm |
| | ASTM D2047 | SCOF ≥0.8 |
| Abrasion Resistance | EN 13845 | 50,000 cycles |
| | EN 13501-1 | Class BfI-S1 |
| D+: +- F: | ASTM E648 | Class 1 |
| Reaction to Fire | CAN/ULC S102.2 | FSV < 300; SDV < 500 |
| | AS ISO 9239-1 | >8.0kW/m ² |
| Static Electrical | EN 1815 | ≤2.0kV Classified as |
| Propensity | EIN 1015 | 'antistatic' |
| Flexibility | ASTM F137 | Conforms |
| Resistance to Light | ASTM F1515 | ΔE ≤ 8.0 - Meets |
| Resistance to Heat | ASTM F1514 | ΔE ≤ 8.0 - Meets |

Sheet Size

| Format | Size | Shades | Coverage per Roll |
|--------|--------------------------|--------|----------------------|
| Sheet | 2m x 20m | 6 | 40m² |
| | (2.187 yds x 21.872 yds) | | (47.834 yds) |

Sustainability

| BRE Green Guide | A+ ENP 472 |
|-------------------------------|----------------------------|
| Generic EN 15804 EPD | Available |
| Recyclable | 100% |
| Recycled Content | Contains recycled material |
| REACH | Compliant |
| Indoor Air Comfort Gold | Eurofins certified product |
| FloorScore | Certified |
| Finnish M1 Classification | Certified |
| AgBB/ABG | Pass |
| Responsible Sourcing BES 6001 | Excellent |


Maintenance Performance

| Resistance to Chemicals | ISO 26987 (EN 423) | Good resistance |
|-------------------------|---|-----------------|
| | ASTM F925 | Good resistance |
| Alco Hand Gels | Compatible for use with most commonly used | |
| | alco-based hand gels | |
| Steam Cleaning | Suitable for steam cleaning on a periodic basis | |

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence $% \left(1\right) =\left(1\right) \left(1\right)$

Polysafe Mosaic PUR







Earthstone 4155 w/r 4155 NCS S 3010-Y40R LRV 39



South Sea 4175 NCS S 5020-R90B LRV 19




NCS S 3502-Y

w/r 4105 LRV 39



LRV 23

NCS S 5500-N




NCS S 4020-B10G

LRV 25

w/r - Weld Rod LRV - Light Reflectance Value NCS - Natural Colour System









Let us help you

Our history

Founded in 1915, James Halstead plc, the parent company of Polyflor Ltd, was originally a textile company based in Manchester, UK, until the 1950's when it pioneered the development of homogeneous vinyl floorings.



Responsible sourcing

Polyflor is proud to be the first flooring manufacturer to be awarded BES 6001 certification for the Responsible Sourcing of Construction Product, achieving an Excellent rating. This is a recognised standard certified by BRE Global which proves that a manufacturer is using materials that have been responsibly sourced and acts responsibly.



Help is here

Polyflor has dedicated and experienced personnel within its sales, marketing, technical and design departments, to provide comprehensive support to our customers. We are ready to assist with queries on topics such as product selection specification, installation, performance an ongoing maintenance.




Product innovation

In collaboration with industry partners, Polyflor is working on developments in new products and technologies. Recent launches include a non-directional homogeneous sheet collection that keeps waste to a minimum and loose lay adhesive-free safety sheet and high design tile and plank flooring for quick turnaround projects.



Design service

and advise colours and product choices when you're looking to create a memorable floor design. We offer the precision and the flexibility of waterjet cutting to



BIM objects

A selection of Polyflor's market leading product ranges are now available as Building Information Modelling (BIM) objects.

These objects can be downloaded free of charge from the NBS National BIM Library or www.polyflor.com/bim and www.bimobject.com

Commitment to our supply chain

With ISO 9001 Quality Management and ISO 14001 accreditation, the availability of consistent, good quality products is ensured. We test our products to a wide range of international standards, including slip resistance and VOC emissions, to back-up their performance.



Flooring when you need it

Thanks to Polyflor's extensive warehousing facilities and commitment to holding large quantities of stock, we can react quickly to orders and offer faster lead times for our customers. Polyflor products are readily available worldwide through our wide network of supporting agents and wholesale partners.



Training at Polyflor

To encourage best practice throughout the flooring sector, Polyflor offers both floor laying and floor cleaning courses in a purpose-built facility. For more info contact info@polyflor.ca







Recycling vinyl

Polyflor is a co-founding and funding member of Recofloor, the UK flooring industry's leading vinyl take back scheme for waste vinyl off-cuts and smooth uplifted flooring. For more information about the Recofloor recycling scheme visit www.recofloor.org



Low maintenance

Polyflor's PUR polyurethane reinforcement is cross linked and UV cured for enhanced protection, optimum appearance retention and superior cleaning benefits such as an easier more environmentally friendly maintenance regime. For further in-depth and tailored information on floor maintenance, visit www.polyflor.ca



Free samples

o request free individual product amples of any of Polyflor's flooring ollections, visit www.polyflor.ca or mail us at samples@polyflor.ca .lternatively, you can call the edicated Polyflor Sample Hotline n (905) 364-3000

8



POLYFLOR TM INTERNATIONAL

Australia Polyflor Australia Tel: 1800 777 425 Email: sales@polyflor.com.au

Canada Polyflor Canada Inc. Tel: +1 905 364 3000 Email: sales@polyflor.ca

China Polyflor Hong Kong O/B Polyflor Ltd. Tel: +(852) 2865 0101

Email: info@polyflor.com.hk

Colombia Polyflor Ltd. (LATAM Office) Tel: +57 3223082375 Email: info@polyflor.com

France James Halstead France SAS Tel: +33 (0)8 20 20 32 11 Email: info@jhfrance.fr

Germany objectflor Art und Design Belags GmbH Spain Polyflor Ltd.

Tel: +49 (0) 2236 966 330 Email: info@objectflor.de

India Polyflor India Pvt Ltd. Tel: +91 22 4023 2485 Tel: +91 22 4023 2486

Email: info@polyflor.co.in

Polyflor Ireland Tel: +353 (1) 864 9304 Email: salesireland@polyflor.com

Malaysia Polyflor Martex Tel: 1300 80 7788

Ireland

Email: sales@polyflor.com.my

Middle East Polyflor FZE Tel: +971 50 406 8114 E-mail: aelwakil@polyflorfze.ae

New Zealand Polyflor New Zealand Ltd. Tel: 0800 765 935 Tel: +64 9 269 1111

Email: sales@polyflor.co.nz

Norway Polyflor Nordic Tel: +47 23 00 84 00 Email: firmapost@polyflor.no

Tel: +34 619 949 0<u>5</u>4 Email: info@polyflor.com

Sweden Polyflor Nordic Sweden AB Tel: +46 (0) 300 15820 Email: info@polyflor.se

POLYFLOR CANADA INC.

3209 Orlando Dr, Mississauga Ontario L4V 1C5, Canada

Tel: (905) 364-3000 E-mail: sales@polyflor.ca

> James Halitend FLOORING