

WOOD FX ACOUSTIX PUR

Polysafe Wood FX Acoustix PUR is a high specification, decorative safety vinyl flooring range combining the assurance of slip resistance and acoustic sound insulation.

This collection incorporates a light to dark colour spectrum with non-intrusive safety aggregates to create a safe yet attractive interior.

- Acoustic safety sheet flooring available in 8 colours
- PUR no wax, no finish,
 low maintenance
- Impact sound reduction level of 19dB





Technical Specification

Product Format

| Gauge | ISO 24346 (EN 428) | 3.7mm |
|-----------------------------|--------------------|------------------------|
| Wear Layer | ISO 24340 (EN 429) | 0.65mm |
| Total Weight | ISO 23997 (EN 430) | 2670g/m ² |
| Finish | | PUR |
| Performance Requ | irements | |
| General Performance | ISO 11638 (EN 651) | Conforms |
| Use Area | ISO 10874 (EN 685) | 23, 34, 42 |
| Enhanced Slip Resistance | EN 13845 | ESf |
| | AS 4586 | R10 |
| | RRL Pendulum Test | ≥36 (wet test - |
| | | 4S Rubber / Slider 96) |
| | Surface Roughness | Rz ≥20 μm |
| Abrasion Resistance | EN 13845 | 50,000 cycles |
| | EN 13501-1 | Class Bfl-S1 |
| Reaction to Fire | ASTM E648 | Class 1 |
| | CAN/ULC S102.2 | FSV < 300; SDV < 500 |
| Static Electrical | EN 1015 | ≤2.0kV Classified as |
| Propensity | EN 1815 | 'antistatic' |
| Residual Indentation | ISO 24343-1 | ≤0.20mm |
| | | |

Sheet Size

| Format | Size | Shades | Coverage per Roll |
|--------|--------------------------|--------|----------------------|
| Sheet | 2m x 20m | 8 | 40m² |
| | (2.187 vds x 21.872 vds) | | (47.834 vds) |

Sustainability

| BRE Green Guide | | A+ ENP 415 | | |
|-------------------------|----------|----------------------------|------|--|
| Generic EN 15804 EPD | | Available | | |
| Recyclable | | 100% | | |
| Recycled Content | | 10% | | |
| REACH | | Compliant | | |
| Indoor Air Comfort Gold | | Eurofins certified product | | |
| FloorScore | | Certified | | |
| AgBB/ABG | | Pass | | |
| Responsible Sourcing | BES 6001 | Excellent | | |
| Acoustic Performance | | | | |
| Impact Sound Reduction | | ISO 10140-3 | 19dB | |
| | | | | |

Maintenance Performance


| Resistance to Chemicals | ISO 26987 (EN 423) | Good resistance | |
|-------------------------|---|-----------------|--|
| Alco Hand Gels | Compatible for use with most commonly used | | |
| | alco-based hand gels | | |
| Steam Cleaning | Suitable for steam cleaning on a periodic basis | | |
| | | | |

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products.


The implementation of an effective cleaning regime is the most important defence against infection.

Polysafe Wood fx Acoustix PUR

PARQUET DESIGNS







Parish Oak Parquet 3398 plank size in sheet: 76.2 x 288.6mm w/r 9841 1RV 32



American Oak 3382 plank size in sheet: 100 x 1000mm w/r 3380 LRV 37



Sun Bleached Oak 3384 plank size in sheet: 200 x 1500mm w/r 3372 LRV 31



Rustic Oak 3332 plank size in sheet: 83 x 333/666mm w/r 3330 LRV 26



Silver Oak 3352 plank size in sheet: 83 x 333/666mm w/r 3237 LRV 23



European Oak 3342 plank size in sheet: 100 x 1000mm



Aged Oak 3389 plank size in sheet: 200 x 1500mm

w/r - Weld Rod LRV - Light Reflectance Value









Let us help you

Our history

Founded in 1915, James Halstead plc, the parent company of Polyflor Ltd, was originally a textile company based in Manchester, UK, until the 1950's when it pioneered the development of homogeneous vinyl floorings.



Responsible sourcing

Polyflor is proud to be the first flooring manufacturer to be awarded BES 6001 certification for the Responsible Sourcing of Construction Product, achieving an Excellent rating. This is a recognised standard certified by BRE Global which proves that a manufacturer is using materials that have been responsibly sourced and acts responsibly.



Help is here

Polyflor has dedicated and experienced personnel within its sales, marketing, technical and design departments, to provide comprehensive support to our customers. We are ready to assist with queries on topics such as product selection specification, installation, performance an ongoing maintenance.




Product innovation

In collaboration with industry partners,
Polyflor is working on developments in new
products and technologies. Recent launches
include a non-directional homogeneous sheet
collection that keeps waste to a minimum
and loose lay adhesive-free safety sheet and
high design tile and plank flooring for quick



Design service

Our designers can provide visuals and advise colours and product choices when you're looking to create a memorable floor design. We offer the precision and the flexibility of waterjet cutting to produce any design you require



BIM objects

A selection of Polyflor's market leading product ranges are now available as Building Information Modelling (BIM) objects.

These objects can be downloaded free of charge from the NBS National BIM Library or www.polyflor.com/bim and www.bimobject.com

Commitment to our supply chain

With ISO 9001 Quality Management and ISO 14001 accreditation, the availability of consistent, good quality products is ensured. We test our products to a wide range of international standards, including slip resistance and VOC emissions, to back-up their performance.



Flooring when you need it

Thanks to Polyflor's extensive warehousing facilities and commitment to holding large quantities of stock, we can react quickly to orders and offer faster lead times for our customers. Polyflor products are readily available worldwide through our wide network of supporting agents and wholesale partners.



Training at Polyflor

To encourage best practice throughout the flooring sector, Polyflor offers both floor laying and floor cleaning courses in a purpose-built facility. For more info contact info@polyflor.ca







Recycling vinyl

Polyflor is a co-founding and funding member of Recofloor, the UK flooring industry's leading vinyl take back scheme for waste vinyl off-cuts and smooth uplifted flooring. For more information about the Recofloor recycling scheme visit www.recofloor.org



Low maintenance

Polyflor's PUR polyurethane reinforcement is cross linked and UV cured for enhanced protection, optimum appearance retention and superior cleaning benefits such as an easier more environmentally friendly maintenance regime. For further in-depth and tailored information on floor maintenance, visit www.polyflor.ca



Free samples

To request free individual product samples of any of Polyflor's flooring collections, visit www.polyflor.ca or email us at samples@polyflor.ca Alternatively, you can call the dedicated Polyflor Sample Hotline on 1 905-364-3000



POLYFLOR INTERNATIONAL

Australia Polyflor Australia Tel: 1800 777 425 Email: sales@polyflor.com.au

Canada Polyflor Canada Inc. Tel: +1 905 364 3000 Email: sales@polyflor.ca

Polyflor Hong Kong O/B Polyflor Ltd. Tel: +(852) 2865 0101 Email: info@polyflor.com.hk

Polyflor Ltd. (LATAM Office) Tel: +57 3223082375 Email: info@polyflor.com

James Halstead France SAS Tel: +33 (0)8 20 20 32 11 Email: info@jhfrance.fr

Germany objectflor Art und Design Belags GmbH Tel: +49 (0) 2236 966 330 Email: info@objectflor.de

Polyflor India Pvt Ltd. Tel: +91 22 4023 2485 Tel: +91 22 4023 2486 Email: info@polyflor.co.in Ireland Polyflor Ireland Tel: +353 (1) 864 9304 Email: salesireland@polyflor.com

Malaysia Polyflor Martex Tel: 1300 80 7788 Email: sales@polyflor.com.my

Middle East Polyflor FZE Tel: +971 50 406 8114 E-mail: aelwakil@polyflorfze.ae

New Zealand Polyflor New Zealand Ltd. Tel: 0800 765 935 Tel: +64 9 269 1111 Email: sales@polyflor.co.nz

Norway Polyflor Nordic Tel: +47 23 00 84 00 Email: firmapost@polyflor.no

Spain Polyflor Ltd. Tel: +34 619 949 054 Email: info@polyflor.com

Polyflor Nordic Sweden AB Tel: +46 (0) 300 15820 Email: info@polyflor.se

POLYFLOR CANADA INC.

3209 Orlando Dr, Mississauga Ontario L4V 1C5, Canada

Tel: (905) 364-3000 E-mail: sales@polyflor.ca

James Halstend™