

Polysafe™

RECEPTION ↑
EXAM ROOMS 1-5 →
PEDIATRICS →

WELCOM

RECEPTION

WOOD FX PUR

WOOD FX PUR

Polysafe Wood FX is a distinctive collection developed to capture the beauty and authenticity of material surfaces with the built-in reassurance of sustainable wet slip resistance.

This heavy-duty collection features commercial floor designs with high clarity stone and concrete effects across a range of a light to dark colour spectrum.

Typical installations are within education, healthcare, social housing & office sectors.

- Safety sheet flooring available in 12 colours
- PUR no wax, no finish, low maintenance
- R10 slip resistance per standard DIN 51130



Blanched Oak 3397



Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	2.0mm
Wear Layer	ISO 24340 (EN 429)	0.70mm
Total Weight	ISO 23997 (EN 430)	2780g/m ²
Finish	PUR	
Performance Requirements		
General Performance	EN 13845	Conforms
	ASTM F1303	Type I, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845	ESf
	RRL Pendulum Test	≥36 (wet test - 45 Rubber / Slider 96)
	DIN 51130 /	R10
	DIN EN 16165 Ann. B	
	AS 4586	R10
	Surface Roughness	Rz ≥20µm
	ASTM D2047	SCOF ≥0.8
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1
	CAN/ULC S102.2	FSV < 300; SDV < 500
	AS ISO 9239-1	>8.0kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750 psi)
Flexibility	ASTM F137	1.5" Pass
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sheet Size

Format	Size	Shades	Coverage per Roll
Sheet	2m x 20m (2.187 yds x 21.872 yds)	16	40m ² (47.834 yds)

Sustainability		
BRE Green Guide		A+ ENP 415
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		10%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent

Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		

Hygiene		
Bacterial Resistance	ISO 846 Part C	Does not favour growth

Polysafe Wood fx PUR

PARQUET DESIGNS				
Eton Oak Parquet 3392* plank size in sheet: 76.2 x 288.6mm w/r 9822 LRV 24	Parish Oak Parquet 3391* plank size in sheet: 76.2 x 288.6mm w/r 9841 LRV 32	Newport Oak 3394 plank size in sheet: 167 x 1500mm w/r 9838 LRV 30	Blanched Oak 3397 plank size in sheet: 200 x 1000mm w/r 3113 LRV 42	Oslo Oak 3396 plank size in sheet: 167 x 1500mm w/r 9829 LRV 32
Sun Bleached Oak 3372* plank size in sheet: 200 x 1500mm w/r 3372 LRV 31	Silver Oak 3357* plank size in sheet: 83 x 333/666mm w/r 3237 LRV 23	Oiled Oak 3374 plank size in sheet: 166 x 1500mm w/r 3374 LRV 37	Roasted Limed Ash 3375 plank size in sheet: 166 x 1500mm w/r 9831 LRV 30	Tropical Pine 3376 plank size in sheet: 166 x 1500mm w/r 9822 LRV 22
American Oak 3387* plank size in sheet: 100 x 1000mm w/r 3380 LRV 37	Rustic Oak 3337* plank size in sheet: 83 x 333/666mm w/r 3330 LRV 26	Classic Oak 3107 plank size in sheet: 166 x 1500mm w/r 3330 LRV 29	European Oak 3347* plank size in sheet: 100 x 1000mm w/r 3340 LRV 23	Aged Oak 3373* plank size in sheet: 200 x 1500mm w/r 9824 LRV 9
Nero Oak 3371 plank size in sheet: 125 x 1000mm w/r 9842 LRV 7				

w/r - Weld Rod

LRV - Light Reflectance Value



Sun Bleached Oak 3372



American Oak 3387 | Brazilian Walnut 3997



Rustic Oak 3337



Warm Beech 3297

All you need to know

Our history

Founded in 1915, James Halstead plc, the parent company of Polyflor Ltd, was originally a textile company based in Manchester, UK, until the 1950's when it pioneered the development of homogeneous vinyl floorings.



Responsible sourcing

Polyflor is proud to be the first flooring manufacturer to be awarded BES 6001 certification for the Responsible Sourcing of Construction Product, achieving an Excellent rating. This is a recognised standard certified by BRE Global which proves that a manufacturer is using materials that have been responsibly sourced and acts responsibly.




Help is here

Polyflor has dedicated and experienced personnel within its sales, marketing, technical and design departments, to provide comprehensive support to our customers. We are ready to assist with queries on topics such as product selection, specification, installation, performance and ongoing maintenance.




Product innovation

In collaboration with industry partners, Polyflor is working on developments in new products and technologies. Recent launches include a non-directional homogeneous sheet collection that keeps waste to a minimum and loose lay adhesive-free safety sheet and high design tile and plank flooring for quick turnaround projects.



Design service

Our designers can provide visuals and advise colours and product choices when you're looking to create a memorable floor design. We offer the precision and the flexibility of waterjet cutting to produce any design you require.



BIM objects

A selection of Polyflor's market leading product ranges are now available as Building Information Modelling (BIM) objects. These objects can be downloaded free of charge from the NBS National BIM Library or www.polyflor.com/bim and www.bimobject.com

Commitment to our supply chain

With ISO 9001 Quality Management and ISO 14001 accreditation, the availability of consistent, good quality products is ensured. We test our products to a wide range of international standards, including slip resistance and VOC emissions, to back-up their performance.



Flooring when you need it

Thanks to Polyflor's extensive warehousing facilities and commitment to holding large quantities of stock, we can react quickly to orders and offer faster lead times for our customers. Polyflor products are readily available worldwide through our wide network of supporting agents and wholesale partners.



Training at Polyflor

To encourage best practice throughout the flooring sector, Polyflor offers both floor laying and floor cleaning courses in a purpose-built facility. For more info contact info@polyflor.ca



Recycling vinyl

Polyflor is a co-founding and funding member of Recofloor, the UK flooring industry's leading vinyl take back scheme for waste vinyl off-cuts and smooth uplifted flooring. For more information about the Recofloor recycling scheme visit www.recofloor.org



Low maintenance

Polyflor's PUR polyurethane reinforcement is cross linked and UV cured for enhanced protection, optimum appearance retention and superior cleaning benefits such as an easier more environmentally friendly maintenance regime. For further in-depth and tailored information on floor maintenance, visit www.polyflor.ca



Free samples

To request free individual product samples of any of Polyflor's flooring collections, visit www.polyflor.ca or email us at samples@polyflor.ca. Alternatively, you can call the dedicated Polyflor Sample Hotline on (905) 364-3000



Aged Oak 3373



Silver Oak 3357

POLYFLOR™ INTERNATIONAL

Australia
Polyflor Australia
Tel: 1800 777 425
Email: sales@polyflor.com.au

Canada
Polyflor Canada Inc.
Tel: +1 905 364 3000
Email: sales@polyflor.ca

China
Polyflor Hong Kong O/B Polyflor Ltd.
Tel: +(852) 2865 0101
Email: info@polyflor.com.hk

Colombia
Polyflor Ltd. (LATAM Office)
Tel: +57 3223082375
Email: info@polyflor.com

France
James Halstead France SAS
Tel: +33 (0)8 20 20 32 11
Email: info@jhfrance.fr

Germany
objectflor Art und Design Belags GmbH
Tel: +49 (0) 2236 966 330
Email: info@objectflor.de

Sweden
Polyflor Nordic Sweden AB
Tel: +46 (0) 300 15820
Email: info@polyflor.se

Ireland
Polyflor Ireland
Tel: +353 (1) 864 9304
Email: salesireland@polyflor.com

Malaysia
Polyflor Martex
Tel: 1300 80 7788
Email: sales@polyflor.com.my

Middle East
Polyflor FZE
Tel: +971 50 406 8114
E-mail: aelwakil@polyflorfze.ae

New Zealand
Polyflor New Zealand Ltd.
Tel: 0800 765 935
Tel: +64 9 269 1111
Email: sales@polyflor.co.nz

Norway
Polyflor Nordic
Tel: +47 23 00 84 00
Email: firmapost@polyflor.no

Spain
Polyflor Ltd.
Tel: +34 619 949 054
Email: info@polyflor.com

POLYFLOR CANADA INC.

3209 Orlando Dr, Mississauga Ontario
L4V 1C5, Canada

Tel: (905) 364-3000

E-mail: sales@polyflor.ca

www.polyflor.ca

James Halstead™
FLOORING