



Geotone QuickLay

LOOSE LAY RESILIENT FLOORING





Geotone QuickLay

Loose Lay flooring, a
Sustainable solution for
Quick Turnaround projects

Introducing Geotone QuickLay, the latest addition to the loose lay family of innovative floor coverings from Polyflor.

A premium, versatile and practical solution, ideal for quick turnaround projects, adhesive-free Geotone QuickLay combines **Easy Fit Technology**, **Low Maintenance** benefits and is optimised for **Sustainable Performance**.

Available in 2m x 20m rolls, Geotone QuickLay enables busy public spaces to be re-occupied and ready for use again on the same day, thus minimising downtime and disruption to services and facilities.

Visually, the **design** concept for Geotone QuickLay centres around a common colour scheme, taking inspiration from elements found in the natural world, including pebbles and stones, often linked to forms of wellbeing & comfort.


With a subtle texture and matt finish, for a consistent overall appearance and ideal for open-plan spaces when a unified and cohesive look is required, the cool & fresh, warm & soothing tone-on-tone palette of Geotone QuickLay evokes a sense of calm and rejuvenation within any interior design scheme.

Continuing Polyflor's commitment to the Health & Care sector, Geotone QuickLay is a Dementia Design Accredited Product via the University of Stirling (see page 9 for DSDC ratings by shade), promoting more positive and inclusive environments for those living with a dementia.

Why choose

Geotone QuickLay

Rewriting the rules for laying sheet flooring, without the need for compromise in terms of performance & quality or design & decoration, adhesive-free Geotone QuickLay is an efficient and effective solution that allows busy spaces to get back to business as normal, quickly.



*Grout lines may require further preparation to avoid grin through, for further advice contact Polyflor's technical team on +44 (0) 161 767 1912



Quick turnaround
projects



Adhesive-free
installation



Lay over subfloors
up to 97% RH



Immediate weld
for a seamless finish



Low VOC
emissions



PUR

Superior
cleanability



Suitable for high
traffic areas



100% recyclable
& reusable



Easy Fit Technology

12 steps to the perfect Geotone QuickLay installation



Standard installation tools. Only Polyflor QuickLay recommended double-sided tape should be used.



Sweep or vacuum the floor area, check the condition of the subfloor and make good as necessary. If the substrate is highly porous a suitable primer may be required.



DO NOT peel the tape until the flooring has been laid & measured correctly.

Apply the QuickLay double-sided tape around the perimeter of the room and at any doorways, set 2mm away from the edge of the room.



Use the appropriate method to install Geotone QuickLay in the room. Allow a 25mm overlap at the seams and cut in to form a tight seam.



Measure 37.5mm away from the side of the seam and mark with a straight edge or chalk line.



Apply the QuickLay double-sided tape along the marked seams.

To ensure the QuickLay tape is firmly positioned correctly, simply press down with a hand roller or cork board.



Check you are happy with the positioning of the flooring and the measurements are correct.




Carefully peel away the protective film from all areas where the tape has been applied.



Once complete, place the floor covering into position ensuring a 'neat fit'.

A hand roller or heavy roller can be used at all seams/perimeter immediately after installing to ensure sufficient contact has been made.



Geotone QuickLay can be hot welded at the seams and to coved skirtings upon immediate completion of the installation.



Same Day install & walk

Adhesive-free Geotone QuickLay can be installed directly over damp subfloors (up to 97% RH) which means you can install and walk same day.

The double-sided QuickLay tape is fitted around the perimeter of the room, underneath all seams and doorways securing the flooring in place.

Designed to support health & wellbeing

Research shows there are more than 944,000 people in the UK who are living with a dementia. 1 in 11 people over the age of 65 have a dementia in the UK.

The number of people with a dementia is increasing because people are living longer. It is estimated that by 2030, the number of people with a dementia in the UK will be more than 1 million.

(NHS <https://www.nhs.uk/conditions/dementia/about-dementia/what-is-dementia/>)

Emphasis on designing interiors that are inclusive, future proofed and dementia-friendly, to help promote a more positive environment

that impacts on health and wellbeing, whether within an assisted living facility, for people living at home or staying in hospital, has never been greater.

Choosing the right flooring is key to promoting a more positive and inclusive environment for those living with a dementia.

Polyflor has devised the following 10 principles which reference back to the overarching principles within Health Building Note HBN 08-02, Design Principles for a Dementia-Friendly Environment, here in relation to Geotone QuickLay.

Polyflor: Principles for Dementia-Friendly Flooring	Geotone QuickLay PUR: Designed to promote harmony & wellbeing
1: Develop one continuous flooring surface	The floor can be both seen and experienced as one continuous surface as Geotone QuickLay is a flexible resilient sheet vinyl, in rolls 2m wide by 20m in length that can be installed in large sections. Geotone QuickLay can be welded and walked upon immediately, creating an overall cohesive appearance.
2: Careful use of tonal contrast	As a rule of thumb, the light reflectance value (LRV) should be 30 points difference between surfaces to get good tonal contrast. LRVs range from 10 to 64 enabling tonal contrast with other surfaces, fixtures & fittings.
3: Reduce impact sound	A well-planned acoustic environment enhances the feeling of privacy, safety and comfort. With an Impact Sound Reduction value of 6dB, Geotone QuickLay can contribute to reducing background or reverberation sound within a room. Less noise disturbance is generated through loose lay installation methods.
4: Accentuate colours to give depth	Geotone QuickLay features a selection of light, mid & darker shades which can help in the perception of the size and shape of a room to aid wayfinding.
5: Avoid sensory overload and false steps	Flooring which contributes to sensory overload can confuse the eye and cause a person living with a dementia to perceive a false step. The tone-on-tone design is subtle and consistent across all Geotone QuickLay shades.
6: Reduce sparkle	The blended colours are tonally close creating an almost plain pattern and the matt surface finish for even distribution of light reflectance, helps reduce any unwanted glare, sparkle or shimmer.
7: Promote the use of a matt floor finish	Geotone QuickLay is a matt flooring, and this will help reduce any unwanted glare from natural sunlight, from nearby windows, or artificial lighting.
8: Blend flecks with the tone of the main floor surface	The blended decoration, small in scale is uniform in its allocation reducing any issues which may have arisen from having a larger scale, uneven, random decorative finish.
9: Avoid unpleasant smells and odours	People living with a dementia may have a strong emotional reaction to smells and odours which can lead to confusion and stress and so cleaning & disinfecting of floor coverings is paramount. Featuring a polyurethane reinforcement and combined with a superior closed surface finish, this enhanced protection allows the use of a polish-free maintenance regime for the lifetime of the Geotone QuickLay flooring. Additionally, adhesive-free flooring installation is characterized by no contamination of sensitive areas by dust or associated odours.
10: Provide good transition between differing floor finishes	Correct installation of edging strips minimises problems such as water leakage and trip hazard. Where flooring with a raised emboss is used, ensure that its use is limited to areas where additional safety flooring is required, such as wet rooms and barefoot areas.



Visually Accessible Spaces

When creating inclusive, safe, calm and supportive dementia-led environments, LRVs, NCS and DSDC ratings provide guidance on the reasonable provisions which should be made for people to access and use a building as per Building Regulations.

Geotone QuickLay has met the standards of DSDC Product Accreditation, University of Stirling's Dementia Services Development Centre, awarded Class 1b (17 shades) and 2 rating (1 shade) for dementia design.

Product & weld rod	NCS Reference	LRV's	dsdC Rating
Periwinkle Pink 6280	1015-R20B	64	1b
Glacial Mist 6281	1505-Y20R	62	1b
Pearl Grey 6271	1502-B	62	1b
Prehnite 6278	1510-G40Y	60	1b
Sand Bar 6284	1510-Y40R	59	1b
Alpine Blue 6274	1020-R80B	53	1b
Pebble Time 6267	2500-N	49	1b
Shingle Beach 6282	3005-Y20R	43	1b
Flint Earth 6272	2010-B	42	1b
Toasted Mauve 6285	2020-R60B	40	1b
Aventurine 6279	3020-G30Y	32	1b
Fountain Stone 6268	4500-N	31	1b
Classic Rock 6273	4502-B	26	1b
Volcanics 6283	5005-Y20R	25	1b
Solent Gold 6286	3040-Y50R	25	1b
Paddlestone 6276	3030-R90B	28	1b
Star Sapphire 6277	5030-R90B	13	1b
Magnetite 6269	7500-N	10	2

1b

Totally matt flooring. This will help reduce any unwanted glare from natural sunlight from nearby windows or from artificial lighting. Decorative effect is very small in scale and uniform in its allocation. These colours are tonally close creating an almost plain pattern & can be used throughout.*

2


Magnetite 6269 has been rated 2 due to the dark colour (LRV 10).*

*Bear in mind the need to contrast flooring with walls, skirtings, doors / frames, furniture & sanitary ware. A minimum contrast of 30 units LRV (Light Reflectance Value) is recommended between surfaces

The Collection

Design & decoration

Visually, the design concept for Geotone QuickLay centres around a common colour scheme, taking inspiration from elements found in the natural world, including pebbles and stones, often linked to forms of wellbeing & comfort.




Colour communication

Each shade features a monochromatic colour scheme and is made up of different tones of a single colour that brings into focus the depth and texture of each blended colourway.

Tone-on-tone Geotone QuickLay, with a matt surface finish, evokes a sense of calm and rejuvenation across the broad palette.

With a dedicated **NCS** value - **Natural Colour System®** - the global go-to standard for defining and communicating colours - the same colour can be reproduced across a variety of materials.



Lightness & brightness of colour


While NCS describes the visual characteristics of a colour, **Light Reflectance Value (LRV)** measures the proportion of useful light reflected by an object.

A universal value for visual 'contrast', LRVs help determine the level of contrast between floors, walls and doors. A requirement within Building Regulations, this ensures equal and safe access for visually impaired people and for those living with a dementia.



Maximising the benefits of PUR

Geotone QuickLay incorporates a polyurethane reinforcement, PUR, which protects the floor covering by resisting soiling and scuffing and allows the use of a **polish-free maintenance regime**, for the lifetime of the flooring.



Sustainable Performance

At Polyflor we are constantly reviewing alternatives and new ideas to improve our environments.

Through modern manufacturing practices, vinyl has a low environmental impact. Combined with exceptional functionality and performance characteristics, across many applications and sectors, vinyl is an environmentally sound choice.

Our Goal: Contribution to the Built Environment

To develop 'loose lay' (adhesive-free) products with reduced environmental impact for ease of recycling.


Geotone QuickLay

From ease of installation to its in-use phase of excellent indoor air quality and low VOC emissions, plus the opportunity to both reuse and recycle, Geotone QuickLay is the sustainable solution for quick turnaround projects.

Our commitment to the Health & Care sector

Polyflor is a recommended supplier to the NHS ProCure23 (P23) framework.

With a rich history of supplying UK manufactured products to the NHS from our manufacturing sites in Manchester and Stockton-on-Tees, collaborating with the framework's Principal Supply Chain Partners, our aim remains to continue to deliver best value flooring solutions to the NHS.



Geotone QuickLay Technical Information

Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	2.2mm
Wear Layer	ISO 24340 (EN 429)	1.0mm
Total Weight	ISO 23997 (EN 430)	2700g/m ²
Finish		PUR
Sheet Size	Size	Shades
Sheet	2m x 20m	18
Performance Requirements	Standard	Result
General Performance	ISO 10582 ASTM F1303	Conforms Type II, Grade 1, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 42
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R10 R10 SCOF ≥ 0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 660-2	Group T
Reaction to Fire	EN 13501-1 ASTM E648 CAN/ULC S-102.2 AS ISO 9239-1	Class Bfl-S1 Class 1 FSV < 300; SDV < 500 $>8.0\text{kW/m}^2$
Static Electrical Propensity	EN 1815	$\leq 2.0\text{kV}$ Classified as 'antistatic'
Residual Indentation	ISO 24343-1 ASTM F970 (Modified) ASTM F1914	$\leq 0.10\text{mm}$ $\leq 0.005"$ (750psi) $\leq 0.005"$
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Furniture Leg	ISO 16581 (EN 424)	Complies
Flexibility	ISO 24344 (EN 435) ASTM F137	(Method A) Pass 20mm \varnothing 0.25" Pass
Underfloor Heating		Suitable, max 27°C
Dimensional Stability	ISO 23999 (EN 434)	$\leq 0.40\%$
Light Fastness	ISO 105-B02 (Method 3)	≥ 6
Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$ - Meets
Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$ - Meets
Sustainability	Standard	Result
Recyclable & Reusable		100%
Recycled Content		Contains recycled material
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
Acoustic Performance	Standard	Result
Impact Sound Reduction	ISO 10140-3	6dB
Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance
Alco Hand Gels		Compatible for use with most commonly used alco-based hand gels
Steam Cleaning		Suitable for steam cleaning on a periodic basis
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection.		
Hygiene	Standard	Result
Bacterial Resistance	ISO 846 Part C	Does not favour growth

Designed for Healthcare:

Welcome

Hospital waiting areas put visitors first.


Offering a safe & welcoming space, with access to a variety of seating areas and information, Geotone QuickLay is the solution.



Quick turnaround
projects



Adhesive-free
installation



1.
6273
Classic Rock

LRV 26 w/r 6273
NCS S 4502-B

2.
6267
Pebble Time

LRV 49 w/r 6267
NCS S 2500-N

3.
6276
Paddlestone

LRV 28 w/r 6276
NCS S 3030-R90B

4.
6274
Alpine Blue

LRV 53 w/r 6274
NCS S 1020-R80B

Designed for Aged Care:

Living well

Aged care facilities put residents first.


Offering a safe, supportive and motivational space, Geotone QuickLay is the solution.



Low VOC
emissions



Superior
cleanability



1.
6281
Glacial Mist

LRV 62 w/r 6281
NCS S 1505-Y20R

2.
6279
Aventurine

LRV 32 w/r 6279
NCS S 3020-G30Y

3.
6278
Aventurine

LRV 60 w/r 6278
NCS S 1510-G40Y

4.
6283
Prehnite


LRV 25 w/r 6283
NCS S 5005-Y20R

Designed for Education:

Think about things differently

An art college space puts students first.

Offering an open and airy, inspirational space, Geotone QuickLay is the solution for that creative vibe.



Lay over subfloors
up to 97% RH



100% recyclable
& reusable



1.
6269
Magnetite

LRV 10 w/r 6269
NCS S 7500-N

2.
6268
Fountain Stone

LRV 31 w/r 6268
NCS S 4500-N

3.
6273
Classic Rock

LRV 26 w/r 6273
NCS S 4502-B

4.
6271
Pearl Grey

LRV 62 w/r 6271
NCS S 1502-B

Designed for Retail:

Time to shop



Retail environments put the customer journey first.
Offering an inviting, engaging retail space, Geotone
QuickLay is the solution.



Immediate weld
for a seamless finish



Suitable for high
traffic areas



1.
6282
Shingle Beach

LRV 43 w/r 6282
NCS S 3005-Y20R

2.
6286
Solent Gold

LRV 25 w/r 6286
NCS S 3040-Y50R

3.
6279
Aventurine

LRV 32 w/r 6279
NCS S 3020-G30Y

4.
6281
Glacial Mist

LRV 62 w/r 6281
NCS S 1505-Y20R


Designed for Leisure:

Time to relax

Hospitality puts customer service first.

Offering a welcoming, relaxing space,



Geotone QuickLay is the solution.



Low VOC
emissions



Superior
cleanability



1.
6285
Toasted Mauve

LRV 40 w/r 6285
NCS S 2020-R60B

2.
6280
Periwinkle Pink

LRV 64 w/r 6280
NCS S 1015-R20B

3.
6272
Flint Earth

LRV 42 w/r 6272
NCS S 2010-B

4.
6271
Pearl Grey

LRV 62 w/r 6271
NCS S 1502-B

POLYFLOR™ INTERNATIONAL

Australia

Polyflor Australia
Tel: +61 800 777 425
Email: sales@polyflor.com.au



Canada

Polyflor Canada Inc.
Tel: +1 905 364 3000
Email: sales@polyflor.ca

China

Polyflor North Asia Ltd.
Tel: +852 2865 0101
Email: info@polyflor.com.hk

Colombia

Polyflor Ltd. (LATAM Office)
Tel: +57 314 285 9005
Email: export@polyflor.com

France

James Halstead France SAS
Tel: +33 8 20 20 32 11
Email: info@jhfrance.fr

Germany

objectflor Art und Design Belags GmbH
Tel: +49 2236 966 330
Email: info@objectflor.de

Ireland

Polyflor Ireland
Tel: +353 1 864 9304
Email: salesireland@polyflor.com

Malaysia

Polyflor Malaysia
Tel: +60 1300 80 7788
Email: sales@polyflor.com.my

Middle East

Polyflor Ltd.
Tel: +971 50 406 8114
Email: export@polyflor.com

New Zealand

Polyflor New Zealand Ltd.
Tel: +64 9 269 1111
Email: sales@polyflor.co.nz

Norway

Polyflor Nordic
Tel: +47 23 00 84 00
Email: firmapost@polyflor.no

Spain

Polyflor Ltd.
Tel: +34 619 949 054
Email: export@polyflor.com

Sweden

Polyflor Nordic Sweden AB
Tel: +46 300 15820
Email: info@polyflor.se

POLYFLOR CANADA INC.

3209 Orlando Dr, Mississauga,
Ontario L4V 1C5, Canada

Tel: (905) 364-3000
E-mail: sales@polyflor.ca

www.polyflor.ca

www.polyflor.ca