

Expona Simplay 19dB PUR

PRODUCT SPECIFICATION

Key Features

- > Wood & stone designs
- > Can be laid alongside carpet tiles
- > Can be installed over existing floor coverings
- > In-built IXPE acoustic backing
- > Up to 19dB impact sound reduction
- > Heavy commercial applications & residential



Product Format	Standard	Result
Gauge	ISO 24346 (EN 428)	5.0mm
Wear Layer	ISO 24340 (EN 429)	0.55mm
Total Weight	ISO 23997 (EN 430)	6380g/m ²
Finish		PUR

Plank & Tile Sizes	Size	Shades	Quantity per Box	Coverage per Box/Roll
Plank	177.8mm x 1219.2mm	8	10	2.17m ²
Tile	600mm x 600mm	4	6	2.16m ²

Performance Requirements	Standard	Result
General Performance	ISO 11638 (EN 651)	Conforms
Use Area	ISO 10874 (EN 685)	23, 33, 42
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B AS 4586 Appendix D ASTM D2047	Class DS R10 R10 SCOF ≥0.5
Binder Content	ISO 10582	Type I
Abrasion Resistance	EN 649	Group T
Reaction to Fire	EN 13501-1 ASTM E648 AS ISO 9239-1 CAN/ULC S102.2	Class Cfl-S1 Class 1 >4.5 kW/m ² FSV < 300; SDV < 500
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970 ASTM F1914	≤0.20mm* ≤0.018" @ 750psi ≤0.019"
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Dimensional Stability	ISO 23999 (EN 434) ASTM F2199	≤0.25% Pass
Flexibility	ASTM F137	1" - Pass
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6

Resistance to Light	ASTM F1515	$\Delta E \leq 8.0$ - Meets
Resistance to Heat	ASTM F1514	$\Delta E \leq 8.0$ - Meets

*Average test value from current production.

Sustainability	Standard	Result
BRE Green Guide		A+ Generic
Recyclable & Reusable		100%
Recycled Content		17%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
AgBB/ABG		Pass

Acoustic Performance	Standard	Result
Impact Sound Reduction	ISO 10140-3	19dB
Sound Transmission Coefficient	ASTM E90/492	STC 55
Impact Insulation Class	ASTM E90/492	IIC 56
IXPE Acoustic Layer		1.0mm

Maintenance Performance	Standard	Result
Resistance to Chemicals	ISO 26987 (EN 423) ASTM F925	Good resistance Good resistance

Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.



Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca


© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

Expona Simplay 19dB PUR

RANGE SHADES

177.8mm x 1219.2mm


7" x 48"



White Rustic Pine **9067**



LRV 41



Grey Country Oak **9063**



LRV 40



Natural Rustic Pine **9068**



LRV 22



Blond Country Oak **9064**



LRV 36



American Oak **9062**



LRV 34



Light Cherry **9061**



LRV 26



Natural Ash **9065**



LRV 22





Grey Ash **9066**




LRV 28

600mm x 600mm
23.6" x 23.6"



Cold Grey Concrete 9069 
LRV 18




Warm Grey Concrete 9071 
LRV 23



Light Grey Concrete 9070 
LRV 34



Dark Grey Concrete 9072 
LRV 13

LRV - Light Reflectance Value

 Bevelled Edges

 Colour/Pattern Variation

Polyflor Canada Inc.

3209 Orlando Drive, Mississauga, Ontario, L4V 1C5, Canada • Tel: 905-364-3000 • Email: sales@polyflor.ca • www.polyflor.ca

© At the time of writing and publication of sheet, all the information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.