

STANDARD SMOOTH WITHOUT PUR

MAINTENANCE REGIME



INITIAL CONSTRUCTION CLEAN



OR



- 1 Remove all loose debris.
 - > Ensure that all traces of adhesive are removed from the surface of the floor covering.
 - > Sweep or vacuum to remove dust and grit.



- 2 Damp mop with a neutral detergent.
 - > Diluted to the manufacturer's instructions.



165-300 RPM

- 3 For heavy soiling: Apply a solution of diluted alkaline cleanser and leave for a sufficient time to react with the soiling.
 - > Use a 165 to 300rpm rotary machine to scrub.



- 4 Rinse the floor thoroughly with clean warm water
 - > Pick up with a wet vacuum and leave to dry thoroughly.

2-3

THIN COATS



- 1 Apply two or three thin coats of emulsion polish.
 - > Use either a proprietary polish applicator or Kentucky mop wrung out to prevent over-application of polish.

150 MM




The polish should be applied up to 150mm from the edges of the room, and subsequent coats should be applied at 90 ° to the previous one. The final coat should be applied right up to the edges of the room.

2-3

THIN COATS

- 1 To enable a protective film to develop as quickly as possible, the floor maintainer should be used undiluted for the first 2–3 applications, and, thereafter, in accordance with the manufacturer's instructions.



ROUTINE MAINTENANCE




OR



OR



- 1 Mop, sweep or vacuum to remove dust and loose dirt.
 - > If required, spot remover to remove stubborn marks, with a neutral cleanser.



6

MONTHS

An unsightly build-up of polish should be avoided. The polish should be removed regularly — the interval between application and removal depends on the wear conditions and the number of polish layers (normally six months in heavy traffic areas). Follow the manufacturer's instructions.



REMOVAL OF FLOOR POLISH APPLICATION



ADDITIONAL INFORMATION

POLYFLOR
COVERING THE WORLD

- > Always follow the Health and Safety guidance provided.
- > Regular cleaning is more beneficial to the floor covering and more cost-effective than occasional heavy cleaning.

If in doubt please contact Polyflor Canada.

For more detailed information visit, www.polyflor.ca or e-mail tech@polyflor.ca with any maintenance questions.

Polyflor Canada Inc.
Tel: +1 905 364 3000
Email: sales@polyflor.ca