



VINYL SHEET FLOORING

SAME OR NEXT DAY PICK UP OR
DELIVERY FROM PCW, RICHMOND B.C.





VINYL SHEET FLOORING

SAME OR NEXT DAY PICK UP OR
DELIVERY FROM PCW, RICHMOND B.C

2000 PUR

Stonewall 8230

Lace Blue 8500

CLASSIC MYSTIQUE PUR

Pale Slate 1200

Quartz 1400

Silver Mist 1430

Steel Parade 1550

POLYSAFE VERONA PUR

Rock Salt 5231

Pebble Shore 5233

POLYSAFE APEX 55

Chromite 4202

Biotite 4203

STOCK AVAILABILITY CAN BE SUBJECT TO CHANGE






Classic Mystique PUR

SAME OR NEXT DAY PICK UP OR
DELIVERY FROM PCW, RICHMOND B.C

CLASSIC MYSTIQUE PUR

*Stock availability can be subject to change




Pale Slate 1200 w/r 1200
NCS S 3502-B LRV 47



Quartz 1400 w/r 9340
NCS S 2500-N LRV 50



Silver Mist 1430 w/r 1430
NCS S 1505-Y40R LRV 62



Steel Parade 1550 w/r 1550
NCS S 3500-N LRV 36

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	3250g/m ²
Finish	PUR	
Performance Requirements		
General Performance	ISO 10581	Conforms
	ASTM F1913	Conforms
	ASTM F1700	Class I, Type A
Use Area	ISO 10874 (EN 685)	23, 34, 43
Slip Resistance	EN 13893	Class DS
	DIN 51130 /	R9
	DIN EN 16165 Ann. B	
	AS 4586 Appendix D	R9
	ASTM D2047	SCOF ≥0.6
Binder Content	ISO 10581	Type I
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1
	ASTM E662	<450
	CAN/ULC S102.2	FSV < 300; SDV < 500
	BCA Spec C1.10 Clause 3	Complies
	AS ISO 9239-1	>8.0 kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as ‘antistatic’
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750 psi)
	ISO 24343-1	≤0.10mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Flexibility	ASTM F137	Pass
Underfloor Heating	Suitable, max 27°C	
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability		
BRE Green Guide		A+ ENP 472
GreenTag	LCA Rate Gold Plus	GreenRate level A
Generic EN 15804 EPD	Available	
Recyclable	100%	
Recycled Content	25%	
REACH	Compliant	
Indoor Air Comfort Gold	Eurofins certified product	
FloorScore	Certified	
Finnish M1 Classification	Certified	
AgBB/ABG	Pass	
VOC Emissions	TVOC after 28 days	≤ 10µg/m3
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance		
Impact Sound Reduction	ISO 10140-3	4dB
Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	

All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products. The implementation of an effective cleaning regime is the most important defence against infection. Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.

Hygiene		
Bacterial Resistance	ISO 846 Part C	Does not favour growth
Ease of Radioactive Decontamination	ISO 8690	Excellent

Sheet & Tile Sizes

Format	Size	Coverage per Roll
Sheet	2m x 20m (2.187 yds x 21.872 yds)	40m ² (47.834 yds)

Format	Size	Quantity per Box	Coverage per Box
Tile	300mm x 300mm (11.81" x 11.81")	50	4.5m ² (48.437ft ²)



*Stock availability can be subject to change

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System




2000 PUR

SAME OR NEXT DAY PICK UP OR
DELIVERY FROM PCW, RICHMOND B.C

2000 PUR

*Stock availability can be subject to change



Stonewall 8230
NCS S 4502-B

w/r 8230
LRV 29



Lace Blue 8500
NCS S 2502-Y

w/r 8500
LRV 47

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	2.0mm, 2.5mm
Total Weight	ISO 23997 (EN 430)	2.0mm: 3550g/m ²
		2.5mm: 4552g/m ²
Finish		PUR
Performance Requirements		
General Performance	ISO 10581	Conforms
	ASTM F1913	Conforms
	ASTM F1700	Class I, Type A
Use Area	ISO 10874 (EN 685)	23, 34, 43
	EN 13893	Class DS
Slip Resistance	DIN 51130 /	R9
	DIN EN 16165 Ann. B	
	AS 4586	R9
	ASTM D2047	SCOF ≥0.6
Binder Content	ISO 10581	Type II
Abrasion Resistance	EN 660-2	Group M
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1 (2.0mm)
	ASTM E662	<450 (2.0mm)
	CAN/ULC S102.2	FSV < 300; SDV < 500 (2.0mm)
	AS ISO 9239-1	>8.0 kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750 psi)
	ISO 24343-1	≤0.10mm
Castor Chair (continuous use)	ISO 4918 (EN 425)	Suitable
Flexibility	ASTM F137	Pass
Underfloor Heating		Suitable, max 27°C
Light Fastness	ISO 105-B02 (Method 3)	≥6
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sustainability		
BRE Green Guide		A+ ENP 472
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		25%
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified (2.0mm)
AgBB/ABG		Pass
VOC Emissions	TVOC after 28 days	≤ 10µg/m³
Responsible Sourcing	BES 6001	Excellent

Acoustic Performance		
Impact Sound Reduction	ISO 10140-3	4dB (2.0mm)

Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products.		
The implementation of an effective cleaning regime is the most important defence against infection. Regular light maintenance is more cost-effective than periodic heavy maintenance and more beneficial to the floor covering.		

Hygiene		
Bacterial Resistance	ISO 846 Part C	Does not favour growth
Ease of Radioactive Decontamination	ISO 8690	Excellent (2.0mm)

Sheet & Tile Sizes

Format	Size	Coverage per Roll
Sheet	2.0mm: 2m x 20m (2.187 yds x 21.872 yds)	40m ² (47.834 yds)

Format	Size	Quantity per Box	Coverage per Box
Tile	2.0mm: 300mm x 300mm (11.81" x 11.81")	50	4.5m ² (48.437ft ²)

*Stock availability can be subject to change



w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System



Polysafe Verona PUR: Pure Colours

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	2.0mm
Total Weight	ISO 23997 (EN 430)	2600g/m ²
Finish	PUR	
Performance Requirements		
General Performance	EN 13845	Conforms
	ASTM F 1303	Type II, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845	ESf
	RRL Pendulum Test	≥45 (wet test - 45 Rubber / Slider 96)
	DIN 51130 / DIN EN 16165 Ann. B	R11
	Surface Roughness	Rz ≥20µm
	ASTM D2047	SCOF ≥0.8
	AS 4586 Appendix A	P4
	AS 4586 Appendix D	R11
Abrasion Resistance	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1
	Aus NCC Spec C1.10-3	Complies
	CAN/ULC S102.2	FSV < 300; SDV < 500
Static Electrical Propensity	AS ISO 9239-1	>8.0kW/m ²
	EN 1815	≤2.0kV Classified as ‘antistatic’
Residual Indentation	ASTM F970 (Modified)	≤0.005” (750 psi)
Flexibility	ASTM F137	1.5” Pass
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets
Resistance to Heat	ASTM F1514	ΔE ≤ 8.0 - Meets

Sheet Size

Format	Size	Coverage per Roll
Sheet	2m x 20m (2.187 yds x 21.872 yds)	40m ² (47.834 yds)

Sustainability		
BRE Green Guide		A+ ENP 472
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		Contains recycled material
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent


Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products.		
The implementation of an effective cleaning regime is the most important defence against infection.		
Hygiene		
Bacterial Resistance	ISO 846 Part C	Does not favour growth

Verona Pure Colours PUR

SAME OR NEXT DAY PICK UP OR DELIVERY FROM PCW, RICHMOND B.C


POLYSAFE VERONA PUR

*Stock availability can be subject to change



Rock Salt 5231
NCS S 3000-N

w/r 9858
LRV 43



Pebble Shore 5233
NCS S 5500-N

w/r 5233
LRV 21



Pebble Shore 5233 / Cookie Cream 5201

*Stock availability can be subject to change

w/r - Weld Rod

LRV - Light Reflectance Value

NCS - Natural Colour System



Polysafe Apex 55

Technical Specification

Product Format		
Gauge	ISO 24346 (EN 428)	3.0mm
Total Weight	ISO 23997 (EN 430)	3600g/m ²
Performance Requirements		
General Performance	EN 13845	Conforms
	ASTM F1303	Type II, Grade I, Class B Backing
Use Area	ISO 10874 (EN 685)	23, 34, 43
Enhanced Slip Resistance	EN 13845	ESf
	AS 4586	R12
	RRL Pendulum Test	≥ 55 (wet test - 4S Rubber / Slider 96)
	DIN 51130 / DIN EN 16165 Ann. B	R12
Abrasion Resistance	UNE-ENV 12633	Class 3 (Slider 96)
	EN 13845	50,000 cycles
Reaction to Fire	EN 13501-1	Class Bfl-S1
	ASTM E648	Class 1
	CAN/ULC S102.2	FSV < 300; SDV < 500
	AS ISO 9239-1	>8.0kW/m ²
Static Electrical Propensity	EN 1815	≤2.0kV Classified as 'antistatic'
Residual Indentation	ASTM F970 (Modified)	≤0.005" (750 psi)
Resistance to Light	ASTM F1515	ΔE ≤ 8.0 - Meets

Sheet Size

Format	Size	Coverage per Roll
	2m x 15m (2.187 yds x 16.404 yds)	30m ² (32.808 yds)

Sustainability		
BRE Green Guide		A+ ENP 472
GreenTag	LCA Rate Silver Plus	GreenRate level A
Generic EN 15804 EPD		Available
Recyclable		100%
Recycled Content		Contains recycled material
REACH		Compliant
Indoor Air Comfort Gold		Eurofins certified product
FloorScore		Certified
Finnish M1 Classification		Certified
AgBB/ABG		Pass
Responsible Sourcing	BES 6001	Excellent
Maintenance Performance		
Resistance to Chemicals	ISO 26987 (EN 423)	Good resistance
	ASTM F925	Good resistance
Alco Hand Gels	Compatible for use with most commonly used alco-based hand gels	
Steam Cleaning	Suitable for steam cleaning on a periodic basis	
All Polyflor commercial sheet vinyl ranges provide a continuous, impervious and hygienic flooring solution which can be confidently cleaned in accordance with recommended maintenance procedures and approved maintenance products.		
The implementation of an effective cleaning regime is the most important defence against infection.		
Hygiene		
Bacterial Resistance	ISO 846 Part C	Does not favour growth


SAME OR NEXT DAY PICK UP OR DELIVERY FROM PCW, RICHMOND B.C

POLYSAFE APEX 55

*Stock availability can be subject to change



Chromite 4202
NCS S 6500-N w/r 4760 LRV 15



Biotite 4203
NCS S 8000-N w/r 8640 LRV 6



*Stock availability can be subject to change



Pale Slate 1200



Chromite 4202



VINYL SHEET FLOORING

SAME OR NEXT DAY PICK UP OR
DELIVERY FROM PCW, RICHMOND B.C

POLYFLOR CANADA INC.

Ontario:

3209 Orlando Dr, Mississauga, Ontario
L4V 1C5, Canada

British Columbia:

2351 No. 6 Rd #130, Richmond, British Columbia
V6V 1P3, Canada

Tel: +1 905 364 3000

E-mail: sales@polyflor.ca

www.polyflor.ca

James Halstead
FLOORING